



-NOTES-

1. MAT'L: GRADE 65-45-12 DUCTILE IRON PER ASTM A536 (LATEST REV).
2. HOT DIP GALVANIZE PER ASTM A153 (LATEST REVISION).
3. IDENTIFY PART WITH MANUFACTURER'S ID PER SD SUPPLIER INDEX, COUNTRY OF ORIGIN, AND CAVITY ID. MARK WITH "CHANCE", "GH5N", AND "5/8". ALL LETTERS MUST BE LEGIBLE AFTER GALVANIZING.

CHANCE  
TOLERANCE CHART

CONFIDENTIAL: THIS DRAWING AND ITS CONTENTS ARE CONFIDENTIAL AND THE EXCLUSIVE PROPERTY OF HUBBELL POWER SYSTEMS. NO PUBLICATION, DISTRIBUTION OR COPIES MAY BE MADE WITHOUT THE WRITTEN CONSENT OF HUBBELL POWER SYSTEMS. HUBBELL POWER SYSTEMS UNPUBLISHED. ALL RIGHTS RESERVED UNDER THE COPYRIGHT LAWS.



HUBBELL POWER SYSTEMS

TITLE GUY HOOK 5/8" BOLT			
SIZE SB	DWG NO. SAGH5N	CAT / PART / ASSY NO. GH5N	REV --
DO NOT SCALE THIS DRAWING	DRN BY BERGER	DATE 12/04/12	SHEET 1 OF 1