


-NOTES-

1. MAT'L: GRADE 65-45-12 DUCTILE IRON PER ASTM A536 (LATEST REV).
2. HOT DIP GALVANIZE PER ASTM A153 (LATEST REVISION).
7. IDENTIFY PART WITH MANUFACTURER'S ID PER SD SUPPLIER INDEX, COUNTRY OF ORIGIN, AND CAVITY ID. MARK WITH "CHANCE", "GH6N", AND "3/4". ALL LETTERS MUST BE LEGIBLE AFTER GALVANIZING.

|   |  |  |               |                               |
|---|--|--|---------------|-------------------------------|
| CHANCE<br>TOLERANCE CHART   |  |  <b>HUBBELL POWER SYSTEMS</b><br><small>HUBBELL POWER SYSTEMS, INC.</small> |               |                               |
| <small>CONFIDENTIAL: THIS DRAWING AND ITS CONTENTS ARE CONFIDENTIAL AND THE EXCLUSIVE PROPERTY OF HUBBELL POWER SYSTEMS. NO PUBLICATION, DISTRIBUTION OR COPIES MAY BE MADE WITHOUT THE WRITTEN CONSENT OF HUBBELL POWER SYSTEMS. HUBBELL POWER SYSTEMS UNPUBLISHED ALL RIGHTS RESERVED UNDER THE COPYRIGHT LAWS.</small> |  | TITLE<br>GUY HOOK<br>3/4" BOLT   |               |                               |
|   |  | SIZE<br>SB SAGH6N  | DWG NO.       | CAT / PART / ASSY NO.<br>GH6N |
| DO NOT SCALE THIS DRAWING   |  | DRN BY BERGER  | DATE 12/04/12 | SHEET 1 OF 1                  |