


TABLE		
CAT. NO.	"A" REF	"B" REF
GS16012CC1	12" (30.5 cm)	20" (50.8 cm)
GS16018CC1	18" (45.7 cm)	26" (66.0 cm)
GS16024CC1	24" (61.0 cm)	32" (81.3 cm)
GS16030CC1	30" (76.2 cm)	38" (96.5 cm)
GS16036CC1	36" (91.4 cm)	44" (111.8 cm)
GS16042CC1	42" (106.7 cm)	50" (127.0 cm)
GS16054CC1	54" (137.2 cm)	62" (157.5 cm)
GS16060CC1	60" (152.4 cm)	68" (172.7 cm)
GS16078CC1	78" (198.1 cm)	86" (218.4 cm)
GS16096CC1	96" (243.8 cm)	104" (264.2 cm)
GS16120CC1	120" (304.8 cm)	128" (325.1 cm)
GS16144CC1	144" (365.8 cm)	152" (386.1 cm)

\* GS\_\_\_\_CC1 series has 1 roller as detailed in drawing.  
 For 2 rollers, replace "CC1" in number with "CC2"  
 For no rollers, replace "CC1" in number with "CC"  
 Add "SC" suffix to the end of the catalog number to denote silicone coated rod.

<b>CHANCE</b> <sup>®</sup>	 <b>HUBBELL POWER SYSTEMS, INC.</b>		
	TITLE <b>GUY STRAIN, 16K CLEVIS-CLEVIS, 1 ROLLER</b>		
CONFIDENTIAL: THIS DRAWING AND ITS CONTENTS ARE CONFIDENTIAL AND THE EXCLUSIVE PROPERTY OF HUBBELL POWER SYSTEMS. NO PUBLICATION, DISTRIBUTION, OR COPIES MAY BE MADE WITHOUT THE WRITTEN CONSENT OF HUBBELL POWER SYSTEMS. HUBBELL POWER SYSTEMS UNPUBLISHED ALL RIGHTS RESERVED UNDER THE COPYRIGHT LAWS.	SIZE <b>B</b>	CAT / PART / ASSY NO. <b>SEE CHART</b>	DWG NO. <b>SA_GS16XXXCC1</b>
DO NOT SCALE THIS DRAWING	DRN BY GKT	DATE 12/19/19	REV <b>A</b> SHEET 1 OF 1