

12/01/09 RELEASE TO CAC PRODUCTION PER DCN 16198 REVISIONS THE DESIGN AND DIMENSIONS OF THE PRODUCT SHOWN ON THIS DRAWING ARE SUBJECT TO CHANGE WITHOUT NOTICE TITLE SPECIAL USE SWITCH PULL CHAIN, 2 CIRC, WIRING DEVICE-KELLEMS TOLERANCES UNLESS HUBBELL INCORPORATED OTHERWISE SPECIFIED BRIDGEPORT, CT

DR. BY CAC APP. BY CAC

TR. BY

CHK'D BY

SCALE NONE

DATE 04/01/09

FRACTIONS ± 1/64

DECIMALS ± .005

ANGLES ± 2°

LIST OF PARTS

DESCRIPTION

BASE

MATERIAL

PHENOL I C

FINISH

REPAIRABLE

NON-REPAIRABLE

BLACK

- 4. NIPPLE MATERIAL: POLYCARBONATE, NIPPLE LENGTH: 0.29" [7.5].
- 5. NICKEL COVERED CHAIN AND KNURL NUT.
- 6. LEADS ARE 18 AWG AWM/TEW 105°C 600V, 6" LENGTH; STRIPPED 1/2".
- 7. UL RECOGNIZED; CSA APPROVED.
- 8. RATING:3A, 250VAC, 3A, 125V "L" RATING
  6A, 125VAC.
  DIELECTRIC STRENGTH: 1,000V Meg (MINIMUM)
  INSULATION RESISTANCE: 100 Meg Ohms
- 9. PACKAGING: SEALED IN POLYBAG.