

	LIST OF PARTS	
DESCRIPTION	MATERIAL	FINISH
BLIND END PLATE	ALUMINUM	
SPLICE PLATE	ALUMINUM	
SCREWS	STEEL	GEOMET PLATED
NUTS	STEEL	GEOMET PLATED

CATALOG NUMBER	RAIL HEIGHT NOMINAL (in [mm])	TRAY SIDE RAIL HEIGHT ACTUAL (in [mm])	WIDTH (in [mm])	A (in [mm])	B (in [mm])
LBP412	4 [101.6]	4.25 [108.0]	12 [304.8]	3.75 [95.3]	11.88 [301.8]
LBP418	4 [101.6]	4.25 [108.0]	18 [457.2]	3.75 [95.3]	17.88 [454.2]
LBP424	4 [101.6]	4.25 [108.0]	24 [609.6]	3.75 [95.3]	23.88 [606.6]
LBP612	6 [152.4]	6.25 [158.8]	12 [304.8]	5.75 [146.1]	11.88 [301.8]
LBP618	6 [152.4]	6.25 [158.8]	18 [457.2]	5.75 [146.1]	17.88 [454.2]
LBP624	6 [152.4]	6.25 [158.8]	24 [609.6]	5.75 [146.1]	23.88 [606.6]

NOTES:

- 1. ALL DIMENSIONS ARE IN INCHES AND [MILLIMETERS].
- 2. PRODUCT IS cULus CLASSIFIED.
- 3. SUPPLIED WITH (1) BLIND END PLATE, FASTENERS: (4) Ø3/8" X 3/4" LONG SCREWS & (4) Ø3/8" FLANGED HEX NUTS.
- 4. INSTALL IN ACCORDANCE WITH NEMA STANDARD VE-2 "CABLE TRAY INSTALLATION GUIDELINES".

1	RELEASED PER	٧.	11/2/21	
1	DCN211102014008	AD		
REV	DESCRIPTION	APP	DATE	

THE DESIGN AND DIMENSIONS OF THE PRODUCT SHOWN ON THIS DRAWING ARE SUBJECT TO CHANGE WITHOUT NOTICE. DIMENSIONS ARE IN INCHES [mm].

TITLE

BLIND END, LADDER TRAY



WIRING DEVICE-KELLEMS
HUBBELL INCORPORATED
SHELTON, CT

M-14456

TOLERANCES UNLESS
OTHERWISE SPECIFIED
.XX = ±.01
.XXX= ±.005
ANGLE TOL. ±2

DR. BY AD SCALE NONE
CHK. BY SBW DATE 10/13/21

CAGE CODE 74545