




M-5328 2



CABLE CLAMP HOLDS
CABLE FROM $\varnothing .62$ [15.8]
TO $\varnothing 1.18$ [30.0]

NOTES: (UNLESS OTHERWISE SPECIFIED)

- 1) DIMENSION FORMAT IS: INCHES [mm]
- 2) DIMENSIONS SHOWN ON THIS DRAWING ARE NOMINAL VALUES FOR GENERAL USE ONLY. ACTUAL PART TOLERANCES MUST BE OBTAINED FROM HUBBELL ENGINEERING.

LIST OF PARTS

DESCRIPTION	MATERIAL	FINISH
BODY	NYLON	BLACK
CABLE CLAMP	NYLON	BLACK
BLADE HOLDER	NYLON	NATURAL
BLADES	.100 BRASS	1-WHITE

SUPERSEDES DRAWING
DATED 5-25-71

2 REDRAWN ON CAD WITH CHANGES; TCM 9/14/01
DECIMAL DIMENSIONS WERE
FRACTIONAL ADDED DUAL
DIMENSIONING; ADDED NOTES
1 & 2; REVISED TITLE; COMBO
SCREWS WERE STRAIGHT BLADE;
PER DCN #8682.
JMN TCM

SYM	REVISIONS	APP	DATE

THE DESIGN AND DIMENSIONS OF THE
PRODUCT SHOWN ON THIS DRAWING ARE
SUBJECT TO CHANGE WITHOUT NOTICE

TITLE
ANGLE PLUG
30AMP 125V./250.V.
NEMA 10-30P

TOLERANCES UNLESS OTHERWISE SPECIFIED FRACTIONS $\pm 1/64$ DECIMALS $\pm .005$ ANGLES $\pm 2^\circ$	WIRING DEVICE-KELLEMS HUBBELL INCORPORATED BRIDGEPORT, CT	
	DR. BY EPS	APP. BY JNC
	TR. BY JMN	SCALE 1:1
	CHK'D BY TCM	DATE 9/14/01

REPAIRABLE NON-REPAIRABLE

B M-5328