

CAT. NO.	CLOCK POSITION	RATING	CONTACT SHROUND COLOR	PILOT	UL	CSA
N5100P9		100A 3ØY 120/208V	BLUE	NO	YES	YES

## NOTE:

- 1. THIS DEVICE IS NOT WATERTIGHT.
  2. SHIPPED WITH COVER, CORD CLAMP,
  & CONTACT CARRIER UNASSEMBLED.
  3. TERMINAL WIRE CAPACITY #4 AWG MAX.
  4. COLOR, RATING & CONTACT CONFIGURATION WITH RESPECT TO INDEX KEY OF DEVICE FROM DATUM X-X TO Y-Y IS
  COMPATIBLE WITH I.E.C. 309.

  5. PILOT CONTACT RATING A-600
  (MAKE 7200VA, BREAK 720 VA MAX.)

  6. CORD CAPACITY:

- 1.25 MAX. . 75 MIN DIA. ROUND CORD.

LIS	ST OF PARTS		_		
DESCRIPTION	MATERIAL	FINISH	DIMENSION SHEET FOR CAT. NO.		
HOUSING	NYLON 88		<b>3</b> 5		
COVER	NYLON 86		2		
CORD CLAMP	NYLON 66		蕭		
CONTACT CARRIER CONTACT	POLYESTER BRASS		7 2		
ASSEMBLY SCREWS	5.5.	9	35		
TERMINAL SCREW	S.S.		¥.		
			8		
45 1000	1	400 100000			
,					
			REPAIRABLE ☐ NON-REPAIRABLE ☐		
1 RELEASE PE DCN 12510	R WRV WKV	08/05/05	Ф		
SYM REVISI	ONS A	PP DATE			
THE DESIGN AND DIMENSIONS OF THE PRODUCT SHOWN ON THIS DRAWING ARE SUBJECT TO CHANGE WITHOUT NOTICE					
TITLE 100A PIN & SLEEVE ANGLE PLUG					
TOLERANCES UNLESS OTHERWISE SPECIFIED FRACTIONS ± 1/64	WIRING DEVICE-KELLENS HUBBELL INCORPORATED BRIDGEPORT, CT		4		
DECIMALS ± .005	DR. BY WRV	APP. BY WAV			
ANGLES ± 2"	TR. BY	SCALE 114			
955	CHK'D BY WRV	DATE 7/05			

CODE 74545