


Wiley Grounding Lug Tin-plated copper, low-profile

Grounding Lugs


Constructed of corrosion resistant, tin-plated copper, the Wiley line of grounding lugs are high quality solutions for your grounding needs. The tin-plated lug assures minimum contact resistance and protection against corrosion. The low-profile of the grounding lug allows it to be installed in a variety of positions with one solid or stranded copper wire (14 AWG to 6 AWG), or two copper wires (12 AWG to 10 AWG). Copper wire is secured by a 1/4-28 stainless steel screw, which is horizontal to the tang.

The WEEB® Grounding Lug is installed using stainless steel mounting hardware – standard hex or T-bolt options available. When the hardware is tightened, the WEEB® washer’s specialized teeth embed into coated (e.g. anodized, powder coated, etc.) metal or any electrically conductive metal to establish a reliable electrical connection.

The Wiley Grounding Lug is available unassembled, without installation hardware, and with standard hole sizes of 1/4” and 5/16” (M8). Perfect for galvanized steel applications or anywhere a WEEB® washer is not required.



WEEB® Lug



Wiley Lug

Features and Benefits

- UL 467 Listed, UL 2703 Listed
- Made of corrosion-resistant, tin-plated copper
- Design ensures a quick and easy installation
- Available:
 - With or without WEEB® washer technology
 - Assembled or unassembled
 - With or without installation hardware
- No surface preparation required on the rail or module
- Custom designs available upon request
- Reliability for use throughout the lifetime of the PV system

WEEB® Grounding Lug									
<i>Utilizes proven WEEB® washer technology to bite through most non-conductive coatings.</i>									
Catalog Number	Length inch [mm]	Width inch [mm]	Height inch [mm]	Hole Size inch [mm]	Mounting Hardware	Mounting Hardware Style	Assembled		
WEEB-LUG-6.7	1.57 [40.00]	0.71 [18.00]	0.47 [12.00]	0.27 [6.76]	1/4" hardware included	Hex Bolt	N		
WEEB-LUG-6.7AS						Hex Bolt	Y		
WEEB-LUG-6.7AST						Hex Bolt	Y		
WEEB-LUG-8.0		0.86 [22.00]		0.32 [8.20]	M8 or 5/16" hardware not included	Hex Bolt	N		
WEEB-LUG-8.0AS					5/16" hardware included		Y		
WEEB-LUG-8.0UN				0.71 [18.00]	0.41 [10.30]		M8 or 5/16" hardware not included	N	
WEEB-LUG-8.2							N		
WEEB-LUG-10.3		0.86 [22.00]		M10 or 5/16" hardware not included	N				
Wiley Grounding Lug									
<i>Perfect for galvanized steel applications or anywhere a WEEB® washer is not required.</i>									
WILEYLUG6.7	1.57 [40.00]	0.71 [18.00]	0.47 [12.00]	0.27 [6.76]	1/4" hardware not included	Hex Bolt	N		
WILEYLUG8.0		0.86 [22.00]		0.32 [8.20]	M8 or 5/16" hardware not included				
WILEYLUG8.2		0.709 [18.00]							
WILEYLUG15.8									