

Compression Splices - Service Entrance INSULINK™ Type ES


INSULINK™ Service Entrance Splices, Type ES for AAC (Stranded, Compressed, Compact**), Copper, ACSR, AAAC

Material: Aluminum (Insulated)

Pre-insulated service entrance compression connector installed with OH25 and MD6 HYTOOL™ as well as the 35 and 750 HYPRESS™ tools. Polyethylene caps prevent dirt from accumulating in barrel, grip cable for easy two-hand installation, and seal out moisture. Aluminum connector is anchored to jacket, assuring the connector is under the die when crimping. Nylon jacket insulated connectors electrically and protects against water and weather. Superior color coding. Prefilled with PENETROX™ joint compound and stripsealed to limit oxidation and to increase the life of the connection. Do not use insulated sealed connectors on bare conductors, refer to LINKIT™ connectors.



RUS Accepted



For faster installations use BURNDY® PATRIOT™ family of battery tools, dies and cutters.



■ Not for use on bare conductors.

▲ Accommodates 1/0 stranded aluminum and copper, concentric, compressed and compact conductors.

** Accommodates compact conductors where stated in the table.

Catalog Number	Side A ■			Side B ■			Die Index	Installation Tooling* (# of Crimps per End)		
	ACSR, 6201, 5005	Aluminum & Copper	Color Code	ACSR, 6201, 5005	Aluminum & Copper	Color Code		Dieless OH25	MD6/MD7 Series	35, 750 Series
ES8W8W	—	10 Str. 8 Sol.	Brown	—	10 Str. 8 Sol.	Brown	BG or 5/8	(1)	WBG (1)*	UBG (1)*
ES6W8W		8 Str. 6 Sol. #8 AL Compt	Green	—	8 Str. 6 Sol. #8 AL Compt	Green				
ES6W6W				—	10 Str. 8 Sol.	Brown				
ES4W8W	6	5, 6 Str. 4 Sol.	Blue	—	8 Str. 6 Sol. #8 AL Compt	Green				
ES4W6W				6	5, 6 Str. 4 Sol.	Blue				
ES4W4W				—	10 Str. 8 Sol.	Brown				
ES2W8W	4	3, 4 Str. 2 Sol.	Orange	—	8 Str. 6 Sol. #8 AL Compt	Green				
ES2W6W				6	5, 6 Str. 4 Sol.	Blue				
ES2W4W				4	3, 4 Str. 2 Sol.	Orange				
ES2W2W				—	10 Str. 8 Sol.	Brown				
ES2R8W	2	1 Str. 2 Str. #1 AL Compt #2 AL Compt	Red	—	8 Str. 6 Sol. #8 AL Compt	Green				
ES2R6W				6	5, 6 Str. 4 Sol.	Blue				
ES2R4W				4	3, 4 Str. 2 Sol.	Orange				
ES2R2W				2	1 Str. 2 Str. #1 AL Compt #2 AL Compt	Red				
ES2R2R				1/0, 1	1/0 Str. 1-19 Str.	Yellow				
ES25R6W	1/0, 1	1/0 Str. 1-19 Str.	Yellow	6	5, 6 Str. 4 Sol.	Blue				
ES25R4W				4	3, 4 Str. 2 Sol.	Orange				
ES25R2W				2	2 Str. 1 Str. #1 AL Compt #2 AL Compt	Red				
ES25R2R	—	—	—	1/0, 1	1/0 Str.	Yellow				
ES25A25A	—	1/0 Str. ▲	Yellow	—	—	—				
ES25A4W	6			5, 6 Str. 4 Sol.	Blue					
ES25A2W	4			3, 4 Str. 2 Sol.	Orange					