


3 In. Rigid/IMC Compression Connectors - Uninsulated

Catalog #:
1812



FEATURE BENEFIT

Provides a concrete-tight connection. Also available as an insulated connector.

PRODUCT FEATURES

- Malleable iron construction ensures mechanical protection for the raceway
- Zinc-electroplated for added corrosion protection
- Noninsulated
- Hex compression nuts assure easy wrench installation
- Available in trade sizes 1/2 in. through 4 in.

APPLICATIONS

- For use to bond unthreaded rigid/IMC conduit to a box or enclosure
- RACO 1/2 in. to 4 in. connectors provide concrete-tight connections

CERTIFICATIONS



PRODUCT SPECIFICATIONS

UPC Number:	050169018125
Ea Length/Depth (in.):	3.438
Ea Width (in.):	4.563
Ea Height (in.):	4.563
Wt. Ea. (Lbs.):	3.295
Package Type:	Loose
Package Contents:	1
Product UPC-A Labeled:	No

SHIPPING

I2of5:	50050169018120
Standard Carton Qty:	1
Min Order Qty:	1
Ship Carton Length (in.):	6.125
Ship Carton Width (in.):	5.75
Ship Carton Height (in.):	5.00
Ship Carton Weight (Lbs.):	3.295
Pallet Qty:	336



⚠ WARNING: Cancer -
www.P65Warnings.ca.gov



**COMMERCIAL
CONSTRUCTION**
A Division of Hubbell Incorporated (Delaware)

RACO
3902 W. Sample St.
South Bend, IN 46619
574-234-7151
www.hubbell.com/raco/en

