3-1/2 In. Rigid/IMC Compression Connectors - Uninsulated

Catalog #: 1814



FEATURE BENEFIT

Provides a concrete-tight connection. Also available as an insulated connector.

PRODUCT FEATURES

- Malleable iron construction ensures mechanical protection for the raceway
- Zinc-electroplated for added corrosion protection
- Noninsulated
- · Hex compression nuts assure easy wrench installation
- Available in trade sizes 1/2 in. through 4 in.

APPLICATIONS

- For use to bond unthreaded rigid/IMC conduit to a box or enclosure
- RACO 1/2 in. to 4 in. connectors provide concrete-tight connections

CERTIFICATIONS



PRODUCT SPECIFICATIONS

 UPC Number:
 050169018149

 Ea Length/Depth (in.):
 3.563

 Ea Width (in.):
 5.188

 Ea Height (in.):
 5.188

 Wt. Ea. (Lbs.):
 4.236

 Package Type:
 Loose

 Package Contents:
 1

 Product UPC-A Labeled:
 No

SHIPPING

Pallet Qty:

 I2of5:
 50050169018144

 Standard Carton Qty:
 1

 Min Order Qty:
 1

 Ship Carton Length (in.):
 6.125

 Ship Carton Width (in.):
 5.75

 Ship Carton Height (in.):
 5.00

 Ship Carton Weight (Lbs.):
 4.236

▲ WARNING: Cancer - www.P65Warnings.ca.gov.





336