


**AC CABLE DUPLEX CONNECTORS**90° Squeeze Connectors, Uninsulated Die Cast Zinc
N/A**B69.1**

Catalog #: 2692

APPLICATIONS

For use in dry locations to bond flexible metal conduit to a box or enclosure
 N/A
 For use in dry locations to bond armored cable to a box or enclosure

PRODUCT FEATURES

Rugged metallic construction insures mechanical protection for the raceway

UL LISTED

Standard 514B, File E195969

CSA

C22.2 No. 18

GENERAL PRODUCT INFORMATION

Trade Size: 1/2 in.

DRAWING DIMENSIONS

Dimension A: 7/16 in.
 Dimension B: 2-1/8 in.
 Dimension C: 45/64 in. - 1-5/32 in.
 Dimension D: NO. 8x5/8 in.
 Dimension E: 1/2 in. - 14 NPSM

PACKAGING

Package Type: Carton
 Std. Pkg.: 25
 Ship Carton Qty.: 250
 Product UPC-A Labeled: No
 Weight (Lbs. Per/C): 12.40
 Ship Carton Length (in.): 19.00
 Ship Carton Width (in.): 10.95
 Ship Carton Height (in.): 8.00
 Ctn Weight (Lbs.): 32.50
 UPC Number: 050169026922
 I2of5: 50050169026927