

STRAIGHT CORD CONNECTORS - DIE CAST ZINC

Straight Connectors Die Cast Zinc







Catalog #: 3404DC

APPLICATIONS

For use in outdoor or indoor locations on flexible metallic liquidtight conduit and Type B flexible nonmetallic liquidtight conduit Use to positively bond the conduit to a box or enclosure

PRODUCT FEATURES

Patented split gland-ring is designed to slip onto the conduit quickly gripping the jacket of the conduit, speeding installation, assuring a perfect seal, and preventing pullouts All components are reusable - RACO liquidtight connectors may be easily disassembled and reused after years of service Sealing washer (included) provides a liquidtight seal when terminating the connector in a threadless opening Heavy duty locknut included with every RACO liquidtight connector assures continuity of ground N/A

CULUS

Conduit Fittings 3HNN

GENERAL PRODUCT INFORMATION

Sub Class Uninsulated Trade Size: 1 in

DRAWING DIMENSIONS

Dimension A: Thread Spec. A: Dimension B: Thread Spec. B: Dimension C: Thread Spec. C: Dimension C A/C: Dimension C A/F: Dimension D: Thread Spec. D: Dimension E: Thread Spec. E: Dimension F:

PACKAGING

Package Type: Carton Ship Carton Qty.: 10 Product UPC-A Labeled: No Weight (Lbs. Per/C): Ship Carton Length (in.): 31.80 6.10 Ship Carton Width (in.): 6.10 Ship Carton Height (in.): Ctn Weight (Lbs.): 4.09 3.18

050169980071 UPC Number: 12of5: 50050169980076

Page 1 / 1