


**COLOR-CODED STRAIGHT STRAIN RELIEF CONDUIT AND CORD CONNECTORS**

**Color-Coded Straight Strain Relief Cord Connectors Steel**

**B58.1**



DESCRIPTION	TRADE SIZE	COLOR CODE	SIZE RANGE	Dim A	Dim B
3723-1	1/2"	BROWN	.55-.65	1.44	1.13
3723-2	3/4"	BROWN	.55-.65	1.44	1.13
3723-3	1"	BROWN	.55-.65	1.44	1.13
3723-4	1 1/4"	BROWN	.55-.65	1.44	1.13
3723-5	1 1/2"	BROWN	.55-.65	1.44	1.13
3723-6	2"	BROWN	.55-.65	1.44	1.13
3723-7	2 1/2"	BROWN	.55-.65	1.44	1.13
3723-8	3"	BROWN	.55-.65	1.44	1.13
3723-9	3 1/2"	BROWN	.55-.65	1.44	1.13
3723-10	4"	BROWN	.55-.65	1.44	1.13
3723-11	4 1/2"	BROWN	.55-.65	1.44	1.13
3723-12	5"	BROWN	.55-.65	1.44	1.13
3723-13	5 1/2"	BROWN	.55-.65	1.44	1.13
3723-14	6"	BROWN	.55-.65	1.44	1.13
3723-15	6 1/2"	BROWN	.55-.65	1.44	1.13
3723-16	7"	BROWN	.55-.65	1.44	1.13
3723-17	7 1/2"	BROWN	.55-.65	1.44	1.13
3723-18	8"	BROWN	.55-.65	1.44	1.13
3723-19	8 1/2"	BROWN	.55-.65	1.44	1.13
3723-20	9"	BROWN	.55-.65	1.44	1.13
3723-21	9 1/2"	BROWN	.55-.65	1.44	1.13
3723-22	10"	BROWN	.55-.65	1.44	1.13
3723-23	10 1/2"	BROWN	.55-.65	1.44	1.13
3723-24	11"	BROWN	.55-.65	1.44	1.13
3723-25	11 1/2"	BROWN	.55-.65	1.44	1.13
3723-26	12"	BROWN	.55-.65	1.44	1.13
3723-27	12 1/2"	BROWN	.55-.65	1.44	1.13
3723-28	13"	BROWN	.55-.65	1.44	1.13
3723-29	13 1/2"	BROWN	.55-.65	1.44	1.13
3723-30	14"	BROWN	.55-.65	1.44	1.13
3723-31	14 1/2"	BROWN	.55-.65	1.44	1.13
3723-32	15"	BROWN	.55-.65	1.44	1.13
3723-33	15 1/2"	BROWN	.55-.65	1.44	1.13
3723-34	16"	BROWN	.55-.65	1.44	1.13
3723-35	16 1/2"	BROWN	.55-.65	1.44	1.13
3723-36	17"	BROWN	.55-.65	1.44	1.13
3723-37	17 1/2"	BROWN	.55-.65	1.44	1.13
3723-38	18"	BROWN	.55-.65	1.44	1.13
3723-39	18 1/2"	BROWN	.55-.65	1.44	1.13
3723-40	19"	BROWN	.55-.65	1.44	1.13
3723-41	19 1/2"	BROWN	.55-.65	1.44	1.13
3723-42	20"	BROWN	.55-.65	1.44	1.13
3723-43	20 1/2"	BROWN	.55-.65	1.44	1.13
3723-44	21"	BROWN	.55-.65	1.44	1.13
3723-45	21 1/2"	BROWN	.55-.65	1.44	1.13
3723-46	22"	BROWN	.55-.65	1.44	1.13
3723-47	22 1/2"	BROWN	.55-.65	1.44	1.13
3723-48	23"	BROWN	.55-.65	1.44	1.13
3723-49	23 1/2"	BROWN	.55-.65	1.44	1.13
3723-50	24"	BROWN	.55-.65	1.44	1.13
3723-51	24 1/2"	BROWN	.55-.65	1.44	1.13
3723-52	25"	BROWN	.55-.65	1.44	1.13
3723-53	25 1/2"	BROWN	.55-.65	1.44	1.13
3723-54	26"	BROWN	.55-.65	1.44	1.13
3723-55	26 1/2"	BROWN	.55-.65	1.44	1.13
3723-56	27"	BROWN	.55-.65	1.44	1.13
3723-57	27 1/2"	BROWN	.55-.65	1.44	1.13
3723-58	28"	BROWN	.55-.65	1.44	1.13
3723-59	28 1/2"	BROWN	.55-.65	1.44	1.13
3723-60	29"	BROWN	.55-.65	1.44	1.13
3723-61	29 1/2"	BROWN	.55-.65	1.44	1.13
3723-62	30"	BROWN	.55-.65	1.44	1.13
3723-63	30 1/2"	BROWN	.55-.65	1.44	1.13
3723-64	31"	BROWN	.55-.65	1.44	1.13
3723-65	31 1/2"	BROWN	.55-.65	1.44	1.13
3723-66	32"	BROWN	.55-.65	1.44	1.13
3723-67	32 1/2"	BROWN	.55-.65	1.44	1.13
3723-68	33"	BROWN	.55-.65	1.44	1.13
3723-69	33 1/2"	BROWN	.55-.65	1.44	1.13
3723-70	34"	BROWN	.55-.65	1.44	1.13
3723-71	34 1/2"	BROWN	.55-.65	1.44	1.13
3723-72	35"	BROWN	.55-.65	1.44	1.13
3723-73	35 1/2"	BROWN	.55-.65	1.44	1.13
3723-74	36"	BROWN	.55-.65	1.44	1.13
3723-75	36 1/2"	BROWN	.55-.65	1.44	1.13
3723-76	37"	BROWN	.55-.65	1.44	1.13
3723-77	37 1/2"	BROWN	.55-.65	1.44	1.13
3723-78	38"	BROWN	.55-.65	1.44	1.13
3723-79	38 1/2"	BROWN	.55-.65	1.44	1.13
3723-80	39"	BROWN	.55-.65	1.44	1.13
3723-81	39 1/2"	BROWN	.55-.65	1.44	1.13
3723-82	40"	BROWN	.55-.65	1.44	1.13
3723-83	40 1/2"	BROWN	.55-.65	1.44	1.13
3723-84	41"	BROWN	.55-.65	1.44	1.13
3723-85	41 1/2"	BROWN	.55-.65	1.44	1.13
3723-86	42"	BROWN	.55-.65	1.44	1.13
3723-87	42 1/2"	BROWN	.55-.65	1.44	1.13
3723-88	43"	BROWN	.55-.65	1.44	1.13
3723-89	43 1/2"	BROWN	.55-.65	1.44	1.13
3723-90	44"	BROWN	.55-.65	1.44	1.13
3723-91	44 1/2"	BROWN	.55-.65	1.44	1.13
3723-92	45"	BROWN	.55-.65	1.44	1.13
3723-93	45 1/2"	BROWN	.55-.65	1.44	1.13
3723-94	46"	BROWN	.55-.65	1.44	1.13
3723-95	46 1/2"	BROWN	.55-.65	1.44	1.13
3723-96	47"	BROWN	.55-.65	1.44	1.13
3723-97	47 1/2"	BROWN	.55-.65	1.44	1.13
3723-98	48"	BROWN	.55-.65	1.44	1.13
3723-99	48 1/2"	BROWN	.55-.65	1.44	1.13
3723-100	49"	BROWN	.55-.65	1.44	1.13



Catalog #: 3723-4

**APPLICATIONS**

For use in wet or dry locations to provide a liquidtight and strain relief termination for flexible cord and cable  
 RACO liquidtight strain relief cord connectors are suitable for use in Class I, Div. 2; Class II, Div. 1 & 2; and Class III, Div. 1 & 2 hazardous locations

**PRODUCT FEATURES**

- Neoprene grommets are color-coded by cable diameter allowing for quick and easy identification
- Steel construction provides mechanical strength and durability
- Metallic components are zinc plated for corrosion protection
- Unique Neoprene grommet design - grommet is forced up and around the cord when the nut is tightened creating a liquidtight seal
- Time saving and easy installation - no need to disassemble the fitting for cord installation
- Male tapered thread NPT
- Use RACO locknuts and sealing washers to complete a liquidtight installation on a sheet metal box or panel
- N/A

**CULUS**

UL File E195973

**NEMA**

NEMA 4

**COMPLIANCES**

MSDS  
[www.hubbell-rtb.com/certifications/Hubbell-RACO\\_MSDS\\_for\\_WP\\_Boxes\\_and\\_Fittings,January\\_2015.pdf](http://www.hubbell-rtb.com/certifications/Hubbell-RACO_MSDS_for_WP_Boxes_and_Fittings,January_2015.pdf)

**GENERAL PRODUCT INFORMATION**

Trade Size: 3/4 in.  
 Cable Range: .55 - .65  
 Color Code: Brown

**DRAWING DIMENSIONS**

Dimension A: 1.50  
 Dimension B: 1.25

**PACKAGING**

Package Type: Carton  
 Ship Carton Qty.: 25  
 Product UPC-A Labeled: No  
 Weight (Lbs. Per/C): 17.00  
 Ship Carton Length (in.): 6.00  
 Ship Carton Width (in.): 6.00  
 Ship Carton Height (in.): 4.00  
 Ctn Weight (Lbs.): 4.25  
 UPC Number: 050169983058  
 I2of5: 50050169983053