




## COLOR-CODED STRAIGHT STRAIN RELIEF CONDUIT AND CORD CONNECTORS

### Color-Coded Straight Strain Relief Cord Connectors Steel

B58.1



SKU	TRADE SIZE	COLOR CODE	CABLE RANGE	Dim A	Dim B
3725-1	1/4"	GRAY	.85-.95	1.94	1.12
3725-2	1/2"	GRAY	.85-.95	1.94	1.12
3725-3	3/4"	GRAY	.85-.95	1.94	1.12
3725-4	1"	GRAY	.85-.95	1.94	1.12
3725-5	1 1/4"	GRAY	.85-.95	1.94	1.12
3725-6	1 1/2"	GRAY	.85-.95	1.94	1.12
3725-7	1 3/4"	GRAY	.85-.95	1.94	1.12
3725-8	2"	GRAY	.85-.95	1.94	1.12
3725-9	2 1/4"	GRAY	.85-.95	1.94	1.12
3725-10	2 1/2"	GRAY	.85-.95	1.94	1.12
3725-11	2 3/4"	GRAY	.85-.95	1.94	1.12
3725-12	3"	GRAY	.85-.95	1.94	1.12
3725-13	3 1/4"	GRAY	.85-.95	1.94	1.12
3725-14	3 1/2"	GRAY	.85-.95	1.94	1.12
3725-15	3 3/4"	GRAY	.85-.95	1.94	1.12
3725-16	4"	GRAY	.85-.95	1.94	1.12
3725-17	4 1/4"	GRAY	.85-.95	1.94	1.12
3725-18	4 1/2"	GRAY	.85-.95	1.94	1.12
3725-19	4 3/4"	GRAY	.85-.95	1.94	1.12
3725-20	5"	GRAY	.85-.95	1.94	1.12
3725-21	5 1/4"	GRAY	.85-.95	1.94	1.12
3725-22	5 1/2"	GRAY	.85-.95	1.94	1.12
3725-23	5 3/4"	GRAY	.85-.95	1.94	1.12
3725-24	6"	GRAY	.85-.95	1.94	1.12
3725-25	6 1/4"	GRAY	.85-.95	1.94	1.12
3725-26	6 1/2"	GRAY	.85-.95	1.94	1.12
3725-27	6 3/4"	GRAY	.85-.95	1.94	1.12
3725-28	7"	GRAY	.85-.95	1.94	1.12
3725-29	7 1/4"	GRAY	.85-.95	1.94	1.12
3725-30	7 1/2"	GRAY	.85-.95	1.94	1.12
3725-31	7 3/4"	GRAY	.85-.95	1.94	1.12
3725-32	8"	GRAY	.85-.95	1.94	1.12
3725-33	8 1/4"	GRAY	.85-.95	1.94	1.12
3725-34	8 1/2"	GRAY	.85-.95	1.94	1.12
3725-35	8 3/4"	GRAY	.85-.95	1.94	1.12
3725-36	9"	GRAY	.85-.95	1.94	1.12
3725-37	9 1/4"	GRAY	.85-.95	1.94	1.12
3725-38	9 1/2"	GRAY	.85-.95	1.94	1.12
3725-39	9 3/4"	GRAY	.85-.95	1.94	1.12
3725-40	10"	GRAY	.85-.95	1.94	1.12
3725-41	10 1/4"	GRAY	.85-.95	1.94	1.12
3725-42	10 1/2"	GRAY	.85-.95	1.94	1.12
3725-43	10 3/4"	GRAY	.85-.95	1.94	1.12
3725-44	11"	GRAY	.85-.95	1.94	1.12
3725-45	11 1/4"	GRAY	.85-.95	1.94	1.12
3725-46	11 1/2"	GRAY	.85-.95	1.94	1.12
3725-47	11 3/4"	GRAY	.85-.95	1.94	1.12
3725-48	12"	GRAY	.85-.95	1.94	1.12
3725-49	12 1/4"	GRAY	.85-.95	1.94	1.12
3725-50	12 1/2"	GRAY	.85-.95	1.94	1.12
3725-51	12 3/4"	GRAY	.85-.95	1.94	1.12
3725-52	13"	GRAY	.85-.95	1.94	1.12
3725-53	13 1/4"	GRAY	.85-.95	1.94	1.12
3725-54	13 1/2"	GRAY	.85-.95	1.94	1.12
3725-55	13 3/4"	GRAY	.85-.95	1.94	1.12
3725-56	14"	GRAY	.85-.95	1.94	1.12
3725-57	14 1/4"	GRAY	.85-.95	1.94	1.12
3725-58	14 1/2"	GRAY	.85-.95	1.94	1.12
3725-59	14 3/4"	GRAY	.85-.95	1.94	1.12
3725-60	15"	GRAY	.85-.95	1.94	1.12
3725-61	15 1/4"	GRAY	.85-.95	1.94	1.12
3725-62	15 1/2"	GRAY	.85-.95	1.94	1.12
3725-63	15 3/4"	GRAY	.85-.95	1.94	1.12
3725-64	16"	GRAY	.85-.95	1.94	1.12
3725-65	16 1/4"	GRAY	.85-.95	1.94	1.12
3725-66	16 1/2"	GRAY	.85-.95	1.94	1.12
3725-67	16 3/4"	GRAY	.85-.95	1.94	1.12
3725-68	17"	GRAY	.85-.95	1.94	1.12
3725-69	17 1/4"	GRAY	.85-.95	1.94	1.12
3725-70	17 1/2"	GRAY	.85-.95	1.94	1.12
3725-71	17 3/4"	GRAY	.85-.95	1.94	1.12
3725-72	18"	GRAY	.85-.95	1.94	1.12
3725-73	18 1/4"	GRAY	.85-.95	1.94	1.12
3725-74	18 1/2"	GRAY	.85-.95	1.94	1.12
3725-75	18 3/4"	GRAY	.85-.95	1.94	1.12
3725-76	19"	GRAY	.85-.95	1.94	1.12
3725-77	19 1/4"	GRAY	.85-.95	1.94	1.12
3725-78	19 1/2"	GRAY	.85-.95	1.94	1.12
3725-79	19 3/4"	GRAY	.85-.95	1.94	1.12
3725-80	20"	GRAY	.85-.95	1.94	1.12
3725-81	20 1/4"	GRAY	.85-.95	1.94	1.12
3725-82	20 1/2"	GRAY	.85-.95	1.94	1.12
3725-83	20 3/4"	GRAY	.85-.95	1.94	1.12
3725-84	21"	GRAY	.85-.95	1.94	1.12
3725-85	21 1/4"	GRAY	.85-.95	1.94	1.12
3725-86	21 1/2"	GRAY	.85-.95	1.94	1.12
3725-87	21 3/4"	GRAY	.85-.95	1.94	1.12
3725-88	22"	GRAY	.85-.95	1.94	1.12
3725-89	22 1/4"	GRAY	.85-.95	1.94	1.12
3725-90	22 1/2"	GRAY	.85-.95	1.94	1.12
3725-91	22 3/4"	GRAY	.85-.95	1.94	1.12
3725-92	23"	GRAY	.85-.95	1.94	1.12
3725-93	23 1/4"	GRAY	.85-.95	1.94	1.12
3725-94	23 1/2"	GRAY	.85-.95	1.94	1.12
3725-95	23 3/4"	GRAY	.85-.95	1.94	1.12
3725-96	24"	GRAY	.85-.95	1.94	1.12
3725-97	24 1/4"	GRAY	.85-.95	1.94	1.12
3725-98	24 1/2"	GRAY	.85-.95	1.94	1.12
3725-99	24 3/4"	GRAY	.85-.95	1.94	1.12
3725-100	25"	GRAY	.85-.95	1.94	1.12



Catalog #: 3725-1

### APPLICATIONS

For use in wet or dry locations to provide a liquidtight and strain relief termination for flexible cord and cable. RACO liquidtight strain relief cord connectors are suitable for use in Class I, Div. 2; Class II, Div. 1 & 2; and Class III, Div. 1 & 2 hazardous locations.

### PRODUCT FEATURES

- Neoprene grommets are color-coded by cable diameter allowing for quick and easy identification
- Steel construction provides mechanical strength and durability
- Metallic components are zinc plated for corrosion protection
- Unique Neoprene grommet design - grommet is forced up and around the cord when the nut is tightened creating a liquidtight seal
- Time saving and easy installation - no need to disassemble the fitting for cord installation
- Male tapered thread NPT
- Use RACO locknuts and sealing washers to complete a liquidtight installation on a sheet metal box or panel
- N/A

### CULUS

UL File E195973

### NEMA

NEMA 4

### COMPLIANCES

MSDS  
[www.hubbell-rtb.com/certifications/Hubbell-RACO\\_MSDS\\_for\\_WP\\_Boxes\\_and\\_Fittings,January\\_2015.pdf](http://www.hubbell-rtb.com/certifications/Hubbell-RACO_MSDS_for_WP_Boxes_and_Fittings,January_2015.pdf)

### GENERAL PRODUCT INFORMATION

Trade Size: 1-1/4 in.  
Cable Range: .85 - .95  
Color Code: Gray

### DRAWING DIMENSIONS

Dimension A: 1.94  
Dimension B: 1.88

### PACKAGING

Package Type: Carton  
Ship Carton Qty.: 25  
Product UPC-A Labeled: No  
Weight (Lbs. Per/C): 44.90  
Ship Carton Length (in.): 6.00  
Ship Carton Width (in.): 6.00  
Ship Carton Height (in.): 6.00  
Ctn Weight (Lbs.): 11.23  
UPC Number: 050169983157  
I2of5: 50050169983152