

**COLOR-CODED STRAIGHT STRAIN RELIEF CONDUIT AND CORD CONNECTORS**

**Color-Coded Straight Strain Relief Cord Connectors Steel**

**B58.1**



SPECIFICATIONS							
ROSCON#	TRADE SIZE	COLOR CODE	SIZE RANGE	DIM A	DIM B		
3725-1	1/4"	BLACK	.95 - 1.05	1.40	1.12		
3725-2	1/2"	BLACK	1.10 - 1.25	1.80	1.37		
3725-3	3/4"	BLACK	1.25 - 1.50	2.20	1.62		
3725-4	1"	BLACK	1.50 - 1.75	2.60	1.99		
3725-5	1 1/4"	BLACK	1.75 - 2.00	3.00	2.31		
3725-6	1 1/2"	BLACK	2.00 - 2.25	3.40	2.62		
3725-7	2"	BLACK	2.25 - 2.50	3.80	2.93		
3725-8	2 1/2"	BLACK	2.50 - 2.75	4.20	3.24		
3725-9	3"	BLACK	2.75 - 3.00	4.60	3.55		
3725-10	3 1/2"	BLACK	3.00 - 3.25	5.00	3.86		
3725-11	4"	BLACK	3.25 - 3.50	5.40	4.17		
3725-12	4 1/2"	BLACK	3.50 - 3.75	5.80	4.48		
3725-13	5"	BLACK	3.75 - 4.00	6.20	4.79		
3725-14	5 1/2"	BLACK	4.00 - 4.25	6.60	5.10		
3725-15	6"	BLACK	4.25 - 4.50	7.00	5.41		
3725-16	6 1/2"	BLACK	4.50 - 4.75	7.40	5.72		
3725-17	7"	BLACK	4.75 - 5.00	7.80	6.03		
3725-18	7 1/2"	BLACK	5.00 - 5.25	8.20	6.34		
3725-19	8"	BLACK	5.25 - 5.50	8.60	6.65		
3725-20	8 1/2"	BLACK	5.50 - 5.75	9.00	6.96		
3725-21	9"	BLACK	5.75 - 6.00	9.40	7.27		
3725-22	9 1/2"	BLACK	6.00 - 6.25	9.80	7.58		
3725-23	10"	BLACK	6.25 - 6.50	10.20	7.89		
3725-24	10 1/2"	BLACK	6.50 - 6.75	10.60	8.20		
3725-25	11"	BLACK	6.75 - 7.00	11.00	8.51		
3725-26	11 1/2"	BLACK	7.00 - 7.25	11.40	8.82		
3725-27	12"	BLACK	7.25 - 7.50	11.80	9.13		
3725-28	12 1/2"	BLACK	7.50 - 7.75	12.20	9.44		
3725-29	13"	BLACK	7.75 - 8.00	12.60	9.75		
3725-30	13 1/2"	BLACK	8.00 - 8.25	13.00	10.06		

Catalog #: 3725-2

**APPLICATIONS**

For use in wet or dry locations to provide a liquidtight and strain relief termination for flexible cord and cable  
RACO liquidtight strain relief cord connectors are suitable for use in Class I, Div. 2; Class II, Div. 1 & 2; and Class III, Div. 1 & 2 hazardous locations

**PRODUCT FEATURES**

- Neoprene grommets are color-coded by cable diameter allowing for quick and easy identification
- Steel construction provides mechanical strength and durability
- Metallic components are zinc plated for corrosion protection
- Unique Neoprene grommet design - grommet is forced up and around the cord when the nut is tightened creating a liquidtight seal
- Time saving and easy installation - no need to disassemble the fitting for cord installation
- Male tapered thread NPT
- Use RACO locknuts and sealing washers to complete a liquidtight installation on a sheet metal box or panel
- N/A

**CULUS**

UL File E195973

**NEMA**

NEMA 4

**COMPLIANCES**

MSDS  
[www.hubbell-rtb.com/certifications/Hubbell-RACO\\_MSDS\\_for\\_WP\\_Boxes\\_and\\_Fittings,January\\_2015.pdf](http://www.hubbell-rtb.com/certifications/Hubbell-RACO_MSDS_for_WP_Boxes_and_Fittings,January_2015.pdf)

**GENERAL PRODUCT INFORMATION**

Trade Size: 1-1/4 in.  
Cable Range: .95 - 1.05  
Color Code: Black

**DRAWING DIMENSIONS**

Dimension A: 2.06  
Dimension B: 2.00

**PACKAGING**

Package Type: Carton  
Ship Carton Qty.: 25  
Product UPC-A Labeled: No  
Weight (Lbs. Per/C): 45.00  
Ship Carton Length (in.): 6.00  
Ship Carton Width (in.): 6.00  
Ship Carton Height (in.): 6.00  
Ctn Weight (Lbs.): 11.25  
UPC Number: 050169983164  
I2of5: 50050169983169