COLOR-CODED STRAIGHT STRAIN RELIEF CONDUIT AND CORD CONNECTORS

Color-Coded Straight Strain Relief Cord Connectors Steel

B58.1

Table					
RACO NO.	TRADE SIZE	COLOR CODE	CABLE RANGE	DIM A	DIM B
3720-5	1/2"	RED	150-250	1.44	1.13
3720-1	1/2"	WHITE	250-350	1.44	1.13
3720-2	1/2"	BLUE	350-450	1.44	1.13
3720-3	1/2"	GREEN	450-560	1.44	1.13
3720-4	1/2"	YELLOW	650-750	1.44	1.13
3723-5	3/4"	RED	150-250	1.65	1.25
3723-1	3/4"	WHITE	250-350	1.65	1.25
3723-2	3/4"	BLUE	350-450	1.65	1.25
3723-3	3/4"	GREEN	450-560	1.65	1.25
3723-4	3/4"	YELLOW	650-750	1.65	1.25
3723-6	3/4"	YELLOW	650-750	1.65	1.31
3723-5	3/4"	PURPLE	750-850	1.65	1.31
3724-3	1"	GREEN	450-560	1.75	1.50
3724-1	1"	BROWN	550-650	1.75	1.50
3724-4	1"	YELLOW	650-750	1.75	1.50
3724-5	1"	PURPLE	750-850	1.75	1.50
3724-2	1"	GRAY	850-950	1.94	1.63
3724-6	1"	BLACK	850-1,000	1.94	1.63
3726-5	1-1/4"	PURPLE	750-850	194	1.88
3726-2	1-1/4"	GRAY	850-950	1.94	1.88
3726-1	1-1/4"	BLACK	850-1,000	1.94	1.88
3726-4	1-1/4"	ORANGE	1,050-1,150	2.06	2.00
3726-3	1-1/4"	RED	1,150-1,250	2.06	2.00
3726-7	1-1/4"	WHITE	1,250-1,375	2.06	2.00
3736-5	1-1/2"	BLACK	850-1,000	2.13	2.25
3736-1	1-1/2"	ORANGE	1,050-1,190	2.13	2.25
3736-2	1-1/2"	RED	1,190-1,250	2.13	2.25
3736-3	1-1/2"	WHITE	1,250-1,375	2.13	2.25





Catalog #: 3726-2

APPLICATIONS

For use in wet or dry locations to provide a liquidtight and strain relief termination for flexible cord and cable
RACO liquidtight strain relief cord connectors are suitable for use in Class I, Div. 2; Class II, Div. 1 & 2; and Class III, Div. 1 & 2 hazardous locations

PRODUCT FEATURES

Neoprene grommets are color-coded by cable diameter allowing for quick and easy identification
Steel construction provides mechanical strength and durability
Metallic components are zinc plated for corrosion protection
Unique Neoprene grommet design - grommet is forced up and around the cord when the nut is tightened creating a liquidtight seal
Time saving and easy installation - no need to disassemble the fitting for cord installation
Male tapered thread NPT
Use RACO locknuts and sealing washers to complete a liquidtight installation on a sheet metal box or panel
N/A

CULUS

UL File E195973

NEMA

NEMA 4

COMPLIANCES

MSDS
www.hubbell-rtb.com/certifications/Hubbell-RACO_MSDS_for_WP_Boxes_and_Fittings,January_2015.pdf

GENERAL PRODUCT INFORMATION

Trade Size:	1-1/2 in.
Cable Range:	1.15 - 1.25
Color Code:	Red

DRAWING DIMENSIONS

Dimension A:	2.13
Dimension B:	2.25

PACKAGING

Package Type:	Carton
Ship Carton Qty.:	10
Product UPC-A Labeled:	No
Weight (Lbs. Per/C):	69.60
Ship Carton Length (in.):	6.00
Ship Carton Width (in.):	6.00
Ship Carton Height (in.):	4.00
Ctn Weight (Lbs.):	6.96
UPC Number:	050169983225
I2of5:	50050169983220