


COLOR-CODED 90° STRAIN RELIEF CONDUIT AND CORD CONNECTORS

Color-Coded 90° Strain Relief Cord Connectors Malleable Iron

B58.2





Catalog #: 3794-0

APPLICATIONS

For use in wet or dry locations to provide a liquidtight and strain relief termination for flexible cord and cable RACO liquidtight strain relief cord connectors are suitable for use in Class I, Div. 2; Class II, Div. 1 & 2; and Class III, Div. 1 & 2 hazardous locations

PRODUCT FEATURES

Neoprene grommets are color-coded by cable diameter allowing for quick and easy identification

Malleable Iron construction provides mechanical strength and durability

Metallic components are zinc plated for corrosion protection

Unique Neoprene grommet design - grommet is forced up and around the cord when the nut is tightened creating a liquidtight seal

Time saving and easy installation - no need to disassemble the fitting for cord installation Male tapered thread NPT

Use RACO locknuts and sealing washers to complete a liquidtight installation on a sheet metal box or panel

N/A

CULUS

UL File E195973

NEMA

NEMA 4

GENERAL PRODUCT INFORMATION

Trade Size: 1/2 in. Cable Range: .15 - .25 Color Code: Red

DRAWING DIMENSIONS

2.75 Dimension A: Dimension B: 1.25

PACKAGING

Package Type: Carton Ship Carton Qty.: Product UPC-A Labeled: 25 No Weight (Lbs. Per/C): Ship Carton Length (in.): 29.20 6.00 Ship Carton Width (in.): 6.00 Ship Carton Height (in.): 4.00 Ctn Weight (Lbs.): 7.30

050169983249 UPC Number: 12of5: 50050169983244