Buck-Boost Transformer - Three Phase, 220/230/240 - 208V, 30kVA

By Acme Electric
Catalog # A3030K0310B

Buck-Boost Transformer - Three Phase, 220/230/240 - 208V, 30kVA

Features

- Copper terminations for trouble free operation
- Lower cost solution
- 5-10 times increase in kVA

General

Catalog Number	A3030K0310B
Construction	Encapsulated
Max Temperature Rise	115 Degrees Celsius
Mounting Type	Wall
Primary Voltage	220/230/240
Product Category	Buck-Boost Transformer
Secondary Voltage	208 V
UL Insulation Class	180°C
UPC	047503092408
Winding Material	AL
kVA	30

Dimensions

Dimensions	7.37 in x 19.25 in x 15.21 in
Height	15.21 in
Length	7.37 in
Weight	152 lb
Width	19.25 in

Electrical Ratings

Frequency Rating	60 Hz
Primary Voltage	240 V

Certifications And Compliance

Buy American Compliant	Contact Manufacturer
CSA Standard	C22.2 No 47
Nema Rating	NEMA 3R
UL Standard	UL 506

Logistics

Carton Quantity	1
Pallet Quantity	8

Product Assets

Brochures - 3 Phase Buck Boost Transformers
Brochures - Buck-Boost Transformers
Customer Notices - Prop 65 - Cancer & Reproductive Harm Notice
SDS - HCC SDS
Specifications - A3030K0310B
Terms and Conditions - HCC Terms & Conditions
Video - Product Information Video Series - 3 Phase Buck Boost

©2024 Hubbell Incorporated. All rights reserved