

Industrial Control Transformer .500KVA 208,277 - 120 F3

By Acme Electric Catalog # CE500N006CF3

ICT .500KVA 208,277 - 120 F3

Features

- Encapsulated design protects core & coil assembly from potentially damaging contaminants
- Constructed with high quality silicon steel lamination to minimize core losses and increase efficiency
- Integrally molded terminal blocks with isolation barriers to prevent arc over
- Fuse blocks kits available and easily adaptable
- Series-parallel connecting links save wiring and labor costs

Application

Acme's TB Series Industrial Control Transformers are especially designed to accommodate the momentary current inrush caused when electromagnetic components are energized... without sacrificing secondary voltage stability beyond practical limits.The transformer's windings and internal terminations are encased in a durable thermoplastic end cap, protecting them from potentially damaging moisture, dirt and other ambient contaminants. Acme's TB Series transformers are dry-type, stepdown transformers with the secondary control circuit isolated from the primary line circuit to assure maximum safety.

General

Catalog Number

CE500N006CF3



Color Secondary Voltage UPC

Black 120 V 047503014868

Dimensions

| Dimensions | 5.17 in x 5.25 in x 5.91 in |
|------------|-----------------------------|
| | |
| Height | 5.91 in |
| Length | 5.17 in |
| Weight | 19.2 lb |
| Width | 5.25 in |
| | |

Electrical Ratings

Primary Voltage

208/277 V

Certifications And Compliance

| Certified Listed | • | UL Listed |
|------------------|---|------------|
| | | cUL Listed |

Logistics

| Carton Quantity | 1 |
|-----------------|----|
| Pallet Quantity | 48 |

Product Assets

Specifications - CE500N006CF3



©2024 Hubbell Incorporated. All rights reserved ACME-CE500N006CF3-SPEC-EN | REV 10/2024