Buck-Boost Transformer - Single Phase, 120 X 240 - 12/24V, 7.5kVA

By Acme Electric
Catalog # T211688

Buck-Boost Transformer - Single Phase, 120 X 240 - 12/24V, 7.5kVA

*Representative Image

Features

- Easily configured for numerous applications
- Lower cost solution
- 5-10 times increase in kVA

General

Catalog Number	T211688
Construction	Encapsulated
Max Temperature Rise	115 Degrees Celsius
Mounting Type	Wall
Primary Voltage	120 X 240 V
Product Category	Buck-Boost Transformer
Secondary Voltage	12/24 V
UL Insulation Class	180°C
UPC	047503172506
Winding Material	AL
kVA	7.5

Dimensions

Dimensions	10.84 in x 11.12 in x 20.81 in
Height	20.81 in
Length	10.84 in
Weight	125 lb
Width	11.12 in

Electrical Ratings

Frequency Rating	60 Hz
Primary Voltage	120 X 240 V

Certifications And Compliance

Buy American Compliant	Contact Manufacturer
CSA Standard	C22.2 No 47
Nema Rating	NEMA 3R
UL Standard	UL 506

Logistics

Carton Quantity	1
Pallet Quantity	4

Product Assets

Brochures - Buck-Boost Transformers
Customer Notices - Prop 65 - Cancer & Reproductive Harm Notice
Installation Manuals - SECONDORY VLOTAGE 12/24 BUCK & BOOST TRANSFORMER INSTALLATION INSTRUCTIONS
SDS - HCC SDS
Specifications - T211688
Terms and Conditions - HCC Terms & Conditions
Video - Product Information Video Series - Buck Boost Transformers

©2024 Hubbell Incorporated. All rights reserved