

Low Voltage Distribution Transformer - Single Phase, 600 -120V/240V, 15kVA

By Acme Electric Catalog # T2536171S

Low Voltage Distribution Transformer - Single Phase, 600 - 120V/240V, 15kVA



*Representative Image

Features

- · Quiet operation with sound levels below NEMA standards
- Electrostatic shield for enhanced protection

General

BNFC Taps 2

Construction Encapsulated Electrostatic Shield Shielded

Max Temperature Rise 115 Degrees Celsius

Mounting Type Wall Primary Voltage 600

Product Category Dry Type Distribution

Transformer

Secondary Voltage 120/240 V
Taps % Steps 5%
UL Insulation Class 180°C

UPC 047503734551

Winding Material AL kVA 15

Dimensions

Dimensions 11.59 in x 14.12 in x 16.94 in

Height 16.94 in Length 11.59 in Weight 170 lb Width 14.12 in

Electrical Ratings

Frequency Rating 60 Hz Primary Voltage 600 V

Certifications and Compliance

CSA Standard C22.2 No. 47
Nema Rating NEMA 3R
UL Standard UL 506

Product Assets

3D Models - Group_25

Brochures - General Purpose Dry-Type Distribution

Transformers

Brochures - International Transformers

Catalogs - Acme Electric Catalog - Section 1 - Dry-Type

Distribution Transformers

Customer Notices - Prop 65 - Cancer & Reproductive Harm

Notice

Customer Use Drawings - a-125863 Customer Use Drawings - a-125861 Engineering Drawing - T2536171S

Installation Manuals - Acme Electric Manual A

SDS - HCC_SDS

Terms and Conditions - HCC Terms & Conditions

