Low Voltage Distribution Transformer - Three Phase, 190/200/208/220/240Δ - 400Y/231V, 15kVA

By Acme Electric
Catalog # T379083S

Low Voltage Distribution Transformer - Three Phase, 190/200/208/220/240Δ - 400Y/231V, 15kVA

Features

- Quiet operation with sound levels below NEMA standards
- Electrostatic shield for enhanced protection

General

Catalog Number	T379083S
Construction	Encapsulated
Electrostatic Shield	Shielded
Max Temperature Rise	115 Degrees Celsius
Mounting Type	Floor
Primary Voltage	190 / 200 / 208 / 220 / 240Δ V
Product Category	Dry Type Distribution Transformer
Secondary Voltage	400Y/231 V
UL Insulation Class	180°C
UPC	047503166000
Winding Material	AL
kVA	15

Dimensions

Dimensions	9.03 in x 20.3 in x 18.86 in
Height	18.86 in
Length	9.03 in
Weight	300 lb
Width	20.3 in

Electrical Ratings

Frequency Rating	60 Hz
Primary Voltage	190/200/208/220/240D V

Certifications And Compliance

Buy American Compliant	Contact Manufacturer
CSA Standard	C22.2 No. 47
Nema Rating	NEMA 3R
UL Standard	UL 506

Logistics

Carton Quantity	1
Pallet Quantity	5

Product Assets

Brochures - General Purpose Dry-Type Distribution Transformers
Catalogs - Acme Electric Catalog - Section 1 - Dry-Type Distribution Transformers
Customer Notices - Prop 65 - Cancer & Reproductive Harm Notice
Engineering Drawing - T379083S
SDS - HCC SDS
Specifications - T379083S
Terms and Conditions - HCC Terms & Conditions

©2024 Hubbell Incorporated. All rights reserved