

Industrial Control Transformer .500KVA 240,480,600 - 100,120 F2

By Acme Electric Catalog # TB500N011F2

ICT .500KVA 240,480,600 - 100,120 F2



Dimensions

UPC

Dimensions 5.75 in x 5.25 in x 5.91 in
Height 5.91 in

Length 5.75 in Weight 19.2 lb Width 5.25 in

Electrical Ratings

Frequency Rating 50/60 Hz
Primary Voltage 240/480/600 V

Certifications And Compliance

Certified Listed • UL Listed

cUL Listed

047503018224

Logistics

Carton Quantity 1
Pallet Quantity 12

Product Assets

Catalogs - Acme Electric Catalog - Section 5 - Industrial Control Transformers

Specifications - TB500N011F2

Features

- Encapsulated design protects core & coil assembly from potentially damaging contaminants
- Constructed with high quality silicon steel lamination to minimize core losses and increase efficiency
- Integrally molded terminal blocks with isolation barriers to prevent arc over
- Fuse blocks kits available and easily adaptable
- Series-parallel connecting links save wiring and labor costs

Application

Acme's CE Series Industrial Control Transformers are especially designed to accommodate the momentary current inrush caused when electromagnetic components are energized... without sacrificing secondary voltage stability beyond practical limits. The transformer's windings and internal terminations are encased in a durable thermoplastic end cap, protecting them from potentially damaging moisture, dirt and other ambient contaminants. Acme's TB Series transformers are dry-type, stepdown transformers with the secondary control circuit isolated from the primary line circuit to assure maximum safety.

General

Catalog Number TB500N011F2

Color Black Secondary Voltage 100, 120 V

