

Medium Voltage Transformer - Three Phase, 4160Δ - 600Y//347V, 75kVA

By Acme Electric Catalog # WI075K21

Medium Voltage Transformer - Three Phase, 4160 Δ - 600Y//347V, 75kVA



*Representative Image

General

 $\begin{array}{lll} \text{Catalog Number} & \text{WI075K21} \\ \text{Construction} & \text{Ventilated} \\ \text{Mounting Type} & \text{Floor} \\ \text{Primary Voltage} & 4160\Delta \\ \end{array}$

Product Category Medium Voltage Transformer

 Secondary Voltage
 600Y/347 V

 UPC
 047503098158

Winding Material AL kVA 75

Dimensions

Depth 21.8 in
Height 40.5 in
Weight 760 lb
Width 36.5 in

Electrical Ratings

Efficiency 98.33%
Frequency Rating 60 Hz
Primary Voltage 4160D V

Certifications And Compliance

CSA Standard C22.2 No. 47

Dept of Energy Regulation Meets or exceed U.S. DOE 10

CFR Part 431

Nema Rating NEMA 1 UL Standard UL 1562

Product Assets

Brochures - Medium voltage dry-type transformers Catalogs - Acme Electric Catalog - Section 2 - Medium Voltage Transformers Customer Notices - Prop65_Cancer SDS - HCC SDS

Terms and Conditions - HCC Terms & Conditions

