

Medium Voltage Transformer - Three Phase, 4160Δ - 600Y//347V, 225kVA

By Acme Electric Catalog # WI225K21

Medium Voltage Transformer - Three Phase, 4160 Δ - 600Y//347V, 225kVA



*Representative Image

General

 $\begin{array}{lll} \text{Catalog Number} & \text{W1225K21} \\ \text{Construction} & \text{Ventilated} \\ \text{Mounting Type} & \text{Floor} \\ \text{Primary Voltage} & 4160\Delta \\ \end{array}$

Product Category Medium Voltage Transformer

 Secondary Voltage
 600Y/347 V

 UPC
 047503098691

Winding Material AL kVA 225

Dimensions

 Depth
 26.5 in

 Height
 51.5 in

 Weight
 1480 lb

 Width
 40.5 in

Electrical Ratings

Efficiency 98.82%
Frequency Rating 60 Hz
Primary Voltage 4160D V

Certifications And Compliance

CSA Standard C22.2 No. 47

Dept of Energy Regulation Meets or exceed U.S. DOE 10

CFR Part 431

Nema Rating NEMA 1 UL Standard UL 1562

Product Assets

Brochures - Medium voltage dry-type transformers
Catalogs - Acme Electric Catalog - Section 2 - Medium Voltage
Transformers
Customer Notices - Prop65_Cancer
SDS - HCC SDS
Terms and Conditions - HCC Terms & Conditions

