

Medium Voltage Transformer - Three Phase, 4160Δ - 240Δ V, 300kVA

By Acme Electric Catalog # WI300K17

Medium Voltage Transformer - Three Phase, 4160 Δ - 240 Δ V, 300kVA



*Representative Image

General

 $\begin{array}{lll} \text{Construction} & \text{Ventilated} \\ \text{Mounting Type} & \text{Floor} \\ \text{Primary Voltage} & 4160 \Delta \end{array}$

Product Category Medium Voltage Transformer

Secondary Voltage 240D V

UPC 047503098837

Winding Material AL kVA 300

Dimensions

Depth 32.0 in
Height 66.0 in
Weight 1980 lb
Width 50.5 in

Electrical Ratings

Efficiency 98.93%
Frequency Rating 60 Hz
Primary Voltage 4160D V

Certifications and Compliance

CSA Standard C22.2 No. 47

Dept of Energy Regulation Meets or exceed U.S. DOE 10

CFR Part 431

Nema Rating NEMA 1
UL Standard UL 1562

Product Assets

 $Brochures \hbox{-} Medium Voltage Transformers$

Catalogs - Acme Electric Catalog - Section 2 - Medium Voltage

Transformers

Customer Notices - Prop65_Cancer

Installation Manuals - General Purpose Dry-Type Distribution

Transformer

SDS - HCC SDS

Terms and Conditions - HCC Terms & Conditions

