



\* Representative image

## ALRC008LWE

by Acme Electric

Catalog ID: ALRC008LWE

Prop65\_Cancer&Reproductive

AC Line Reactor - Three Phase, 240 Volts 10% Z - 480 Volts 5% Z - 600 Volts 4% Z, 4594 uH, 8 A, CE Marked, Encapsulated

- Protects from damaging voltage drop
- Eliminates nuisance tripping
- Reduces surges and spike currents
- Longer life for motors and solid state components

### Product Details

#### General

CE Compliant	CE Marked
Construction	Encapsulated
Inductance	4594 uH
Inductance Range	751+ uH
Max Temperature Rise	115 Degrees Celsius
Motor Power	5 HP
Mounting Type	Wall
Primary Voltage	240V / 480V / 600V
Product Category	AC Line Reactor
Reactor Current	8 A
UL Insulation Class	180°C
UPC	047503096574
Winding Material	CU

#### Dimensions

Height	11.5 in
Length	11.5 in
Weight	24 lb
Width	11.5 in

#### Electrical Ratings

Frequency Rating	60 Hz
Primary Voltage	240/480/600 V

#### Certifications and Compliance

CE Compliant	CE Marked
--------------	-----------

CSA Standard	C22.2 No 66
Nema Rating	NEMA 3R
UL Standard	UL 506