



\* Representative image

## ALRC035TBC

by Acme Electric

Catalog ID: ALRC035TBC

Prop65\_Cancer&amp;Reproductive

AC Line Reactor - Three Phase, 240 Volts 10% Z - 480 Volts 5% Z - 600 Volts 4% Z, 1050 uH, 35 A, CE Marked

- Protects from damaging voltage drop
- Eliminates nuisance tripping
- Reduces surges and spike currents
- Longer life for motors and solid state components

### Product Details

#### General

CE Compliant	CE Marked
Inductance	1050 uH
Inductance Range	751+ uH
Max Temperature Rise	115 Degrees Celsius
Motor Power	25 HP
Mounting Hole Width	3.00 in. (7.6 mm)
Primary Voltage	240V / 480V / 600V
Product Category	AC Line Reactor
Reactor Current	35 A
UL Insulation Class	180°C
UPC	047503000564
Winding Material	CU

#### Dimensions

Height	7 in
Length	4.75 in
Weight	23 lb
Width	9 in

#### Electrical Ratings

Frequency Rating	60 Hz
Primary Voltage	240/480/600 V

#### Certifications and Compliance

CE Compliant	CE Marked
CSA Standard	C22.2 No 66

UL Standard	UL 506
-------------	--------