

# HUBBELL Power Systems

## Clevis Eye, Rotated 90-deg

By ANDERSON

Catalog # [879002000](#)

Clevis eyes are used to connect quadrant type deadends to clevis tongue insulators or yoke plates.



\*Representative Image

### Features

- Ultimate strength is 36,000 lbs. (160 kN)
- Eye Hole Opening - 0.8125"
- Length - 5.500"
- Clevis Eye Opening - 0.875" Width
- Clevis Pin Hole Diameter - 0.750"
- Material: body - galvanized ductile iron, Clevis Pin - galvanized steel, Cotter Pin - stainless steel
- Bolt and nut may be substituted for clevis pin by adding suffix "BNK" suffix to the catalog number.

### General

|                            |                  |
|----------------------------|------------------|
| EU RoHS Indicator          | No               |
| Material                   | Ductile Iron     |
| Material - Pin (Clevis)    | Galvanized Steel |
| Material - Pin (Cotter)    | Stainless Steel  |
| Number of Bolt Holes       | 0                |
| Series                     | CE Series        |
| Strength Rating - Ultimate | 36000 lb         |
| Strength Rating - Ultimate | 0 lb             |
| Body                       |                  |
| UPC                        | 096359252603     |

### Dimensions

|                                     |          |
|-------------------------------------|----------|
| Assembly Rating (Ultimate)          | 0 lb     |
| Diameter - Bolt                     | 0 in     |
| Diameter - Eye Hole                 | 0.813 in |
| Diameter - Pin                      | 0 in     |
| Insulator Throat Diameter - Maximum | 0 in     |
| Insulator Throat Diameter - Minimum | 0 in     |
| Insulator Throat Diameter Range     | 0 - 0    |
| Length - Coupling                   | 5.5 in   |
| Length - Pin                        | 0 in     |
| Maximum Adjustment                  | 0 in     |
| Ring Height                         | 0 in     |
| Weight                              | 3.822 lb |
| Width - Eye                         | 0.75 in  |

### Conductor Related

|                              |      |
|------------------------------|------|
| Conductor Diameter - Maximum | 0 in |
| Conductor Spacing            | 0 in |

### Logistics

|                 |     |
|-----------------|-----|
| Pallet Quantity | 480 |
|-----------------|-----|

### Product Assets

[Catalogs - Transmission Connectors Catalog - Full](#)



**A Hubbell brand**

©2024 Hubbell Incorporated. All rights reserved  
AN-879002000-SPEC-EN | REV 6/2024