# **HUBBELL Power Systems**

## Yoke Plate, Triangular

By ANDERSON Catalog # 947604001

Delta configuration yoke plates may be used to bundle two conductors in suspension application with a single string insulator. They may also be used in deadend applications with two strings of insulators and one deadend clamp.



#### **Features**

- Delta Configuration Yoke Plate
- Ultimate Strength is 90,000 lbs.
- 18" hole spacing
- 0.75" thickness
- Material: Galvanized Steel A572 Grade 50

## General

EU RoHS Indicator No Material Steel Number of Bolt Holes 0

Series YPD Series
Strength Rating - Ultimate 90000 lb
Strength Rating - Ultimate 0 lb

Body

UPC 096359253228

#### **Dimensions**

Assembly Rating (Ultimate) O lb
Base Hole Spacing 18 in
Diameter - Apex Hole 1.063 in
Diameter - Base Holes 0.938 in
Diameter - Bolt 0 in
Diameter - Pin 0 in
Insulator / Conductor Hole 18 in
Spacing

O in

Insulator Throat Diameter -

Maximum

Insulator Throat Diameter - 0 in

Minimum

Length - Coupling 6.125 in
Length - Pin 0 in
Maximum Adjustment 0 in
Ring Height 0 in
Thickness at Apex 0.75 in
Thickness at Base 0.75 in
Weight 26.264 lb

## **Conductor Related**

Conductor Diameter - 0 in

Maximum

Conductor Spacing 0 in

### **Product Assets**

Catalogs - Transmission Connectors Catalog - Full

