HUBBELL Power Systems

Terminal, Aluminum Compression

By ANDERSON Catalog # ACF20B

Pure aluminum cast compression terminal for connecting aluminum cable to flat pad. Connector barrel is filled with rubber compatible sealant and enclosed in clear plastic bags.

Features

- NEMA B 2-Hole flat compression terminal
- For use with AAC and ACSR conductor with Cable Diameter Ranges of 0.414-0.448 inches
- Material: Cast Aluminum
- Contact sealant is recommended on the pads.
- For use with conventional tooling.

General

Catalog Number	ACF20B
EU RoHS Indicator	No
Material	Aluminum
Number of Bolt Holes	2
Number of Ground Braid Lug	0
Holes	
Number of Pad Holes	2
Туре	Terminal, Cable to Flat
UPC	096359279327

Dimensions

Angle - Pad	180 °
Base Hole Spacing	0 in
Diameter - Base Holes	0 in
Diameter - Bolt	0 in
Diameter - Inside	0 in
Length - Coupling	0 in
Length Before Compression	0 in
Weight	0.294 lb
Width - Pad	1.5 in



Electrical Ratings

Maximum Current Rating Amps 0 Continuous

Conductor Related

Conductor Compatibility ACSR-Quail-2/0-6/1;AAC-Aster-2/0-7 Conductor Diameter - 0.448 in Maximum Conductor Diameter - Minimum 0.414 in Conductor Diameter Range 0.414 - 0.448 Conductor Type AAC - ACSR

Certifications And Compliance

Buy American Compliant Contact Manufacturer

Logistics

Pallet Quantity 2160

Product Assets

Catalogs - Substation Connectors (SA) Sales Drawings - C-4183 (ACF Bolted Product Family) Specifications - ACF20B Video - Hubbell Power Systems 3D Portal to help with developing 3D models of substation connector products Video - Hubbell Power Systems Quick Ship

