

HUBBELL

Power Systems

Terminal, Aluminum Compression

By ANDERSON
Catalog # [ACF300C](#)

Pure aluminum cast compression terminal for connecting aluminum cable to flat pad. Connector barrel is filled with rubber compatible sealant and enclosed in clear plastic bags.



Features

- NEMA C 4-Hole flat compression terminal
- For use with AAC and ACSR conductor with Cable Diameter Ranges of 0.563-0.630 inches
- Material: Cast Aluminum
- Contact sealant is recommended on the pads.
- For use with conventional tooling.

General

EU RoHS Indicator	No
Material	Aluminum
Number of Bolt Holes	4
Number of Ground Braid Lug Holes	0
Number of Pad Holes	4
Type	Terminal, Cable to Flat
UPC	096359279358

Dimensions

Angle - Pad	180 °
Base Hole Spacing	0 in
Diameter - Base Holes	0 in
Diameter - Bolt	0 in
Diameter - Inside	0 in
Length - Coupling	0 in
Length Before Compression	0 in
Weight	0.784 lb
Width - Pad	3 in

Electrical Ratings

Maximum Current Rating Amps 0
Continuous

Conductor Related

Conductor Compatibility	ACSR-Penguin-4/0-6/1;ACSR-Waxwing-266.8-18/1;AAC-Valerian-250-19;AAC-Laurel-266.8-19
Conductor Diameter - Maximum	0.63 in
Conductor Diameter - Minimum	0.563 in
Conductor Diameter Range	0.563 - 0.63
Conductor Type	AAC ACSR

Logistics

Pallet Quantity	864
-----------------	-----

Product Assets

[Catalogs - Substation Connectors \(SA\)](#)
[Sales Drawings - C-4183 \(ACF Bolted Product Family\)](#)
[Video - Hubbell Power Systems 3D Portal to help with developing 3D models of substation connector products](#)
[Video - Hubbell Power Systems Quick Ship](#)



A Hubbell brand

©2024 Hubbell Incorporated. All rights reserved
AN-ACF300C-SPEC-EN | REV 6/2024