

Terminal, Aluminum Compression

By ANDERSON
Catalog # [ACF350C](#)



Pure aluminum cast compression terminal for connecting aluminum cable to flat pad. Connector barrel is filled with rubber compatible sealant and enclosed in clear plastic bags.

Features

- NEMA C 4-Hole flat compression terminal
- For use with AAC and ACSR conductor with Cable Diameter Ranges of 0.618-0.684 inches
- Material: Cast Aluminum
- Contact sealant is recommended on the pads.
- For use with conventional tooling.

General

Catalog Number	ACF350C
EU RoHS Indicator	No
Material	Aluminum
Number of Bolt Holes	4
Number of Ground Braid Lug Holes	0
Number of Pad Holes	4
Type	Terminal, Cable to Flat
UPC	096359279433

Dimensions

Angle - Pad	180 °
Base Hole Spacing	0 in
Diameter - Base Holes	0 in
Diameter - Bolt	0 in
Diameter - Inside	0 in
Length - Coupling	0 in
Length Before Compression	0 in
Weight	0.784 lb
Width - Pad	3 in

Electrical Ratings

Maximum Current Rating Amps 0
Continuous

Conductor Related

Conductor Compatibility	ACSR-Partridge-266.8-26/7;ACSR-Ostrich-300-26/7;ACSR-Merlin-336.4-18/1;AAC-Tulip-336.1-19;AAC-Daffodil-350-19
Conductor Diameter - Maximum	0.684 in
Conductor Diameter - Minimum	0.618 in
Conductor Diameter Range	0.618 - 0.684
Conductor Type	<ul style="list-style-type: none">• AAC• ACSR

Certifications And Compliance

Buy American Compliant Contact Manufacturer

Logistics

Pallet Quantity 960

Product Assets

[Catalogs - Substation Connectors \(SA\)](#)
[Sales Drawings - C-4183 \(ACF Bolted Product Family\)](#)
[Specifications - ACF350C](#)
[Video - Hubbell Power Systems 3D Portal to help with developing 3D models of substation connector products](#)
[Video - Hubbell Power Systems Quick Ship](#)