

Terminal, Aluminum Compression

By ANDERSON  
Catalog # [ACF400C](#)



Pure aluminum cast compression terminal for connecting aluminum cable to flat pad. Connector barrel is filled with rubber compatible sealant and enclosed in clear plastic bags.

Features

- NEMA C 4-Hole flat compression terminal
- For use with AAC and ACSR conductor with Cable Diameter Ranges of 0.666-0.741 inches
- Material: Cast Aluminum
- Contact sealant is recommended on the pads.
- For use with conventional tooling.

General

Catalog Number	ACF400C
Material	Aluminum
Number of Bolt Holes	4
Number of Ground Braid Lug Holes	0
Number of Pad Holes	4
Type	Terminal, Cable to Flat
UPC	096359279501

Dimensions

Angle - Pad	180 °
Base Hole Spacing	0 in
Diameter - Base Holes	0 in
Diameter - Bolt	0 in
Diameter - Inside	0 in
Dimensions	3 in x 6.5 in x 0.516 in
Height	0.516 in
Length	3 in
Length - Coupling	0 in
Length Before Compression	0 in
Weight	0.68 lb
Width	6.5 in
Width - Pad	3 in

Electrical Ratings

Maximum Current Rating Amps 0  
Continuous

Conductor Related

Conductor Compatibility	ACSR-Ostrich-300-26/7;ACSR-Merlin-336.4-18/1;ACSR-Linnet-336.4-26/7;ACSR-Oriole-336.4-30/7;ACSR-Brahma-203.2-16/19;AAC-Tulip-336.1-19;AAC-Daffodil-350-19;AAC-Canna-397.5-19
Conductor Diameter - Maximum	0.741 in
Conductor Diameter - Minimum	0.666 in
Conductor Diameter Range	0.666 - 0.741
Conductor Type	<ul style="list-style-type: none"><li>• AAC</li><li>• ACSR</li></ul>

Certifications And Compliance

Buy America(n) Qualified	BABA Compliant (All status valid till December 2024)
--------------------------	--

Logistics

Pallet Quantity	864
-----------------	-----

Product Assets

- [Catalogs - Substation Connectors \(SA\)](#)
- [Sales Drawings - CC-10351](#)
- [Specifications - ACF400C](#)
- [Video - Hubbell Power Systems 3D Portal to help with developing 3D models of substation connector products](#)
- [Video - Hubbell Power Systems Quick Ship](#)