

Bus Support, Aluminum Bolted

By ANDERSON
Catalog # [ACS95](#)

Bus Support, Aluminum Bolted, 0.522-0.893 Cable to Insulator,
5 in BC



*Representative Image

Features

- Clamping bolts are Aluminum Alloy
- Clamping bolts have hex-stops for one-wrench installation
- Four Galv-Steel HH Bolts, lock washers and flat washers provided to mount to insulator cap.

General

Material	Aluminum
Material - Clamping Hardware	Aluminum Alloy
Material - Mounting Hardware	Galvanized Steel
Type	Bus Support, Cable to Insulator
UPC	096359280521

Dimensions

Diameter - Bolt Circle	5 in
Weight	3.038 lb

Conductor Related

Conductor Compatibility	ACSR-Penguin-4/0-6/1;ACSR-Waxwing-266.8-18/1;ACSR-Partridge-266.8-26/7;ACSR-Ostrich-300-26/7;ACSR-Merlin-336.4-18/1;ACSR-Linnet-336.4-26/7;ACSR-Oriole-336.4-30/7;ACSR-Chickadee-397.5-18/1;ACSR-Brant-397.5-24/7;ACSR-Ibis-397.5-26/7;ACSR-Lark-397.5-30/7;ACSR-Pelican-477-18/1;ACSR-Flicker-477-24/7;ACSR-Hawk-477-26/7;ACSR-Hen-477-30/7;ACSR-Osprey-556.5-18/1;ACSR-Brahma-203.2-16/19;AAC-Oxlip-4/0-7;AAC-Valerian-250-19;AAC-Laurel-266.8-19;AAC-Tulip-336.1-19;AAC-Daffodil-350-19;AAC-Canna-397.5-19;AAC-Cosmos-477-19;AAC-Syringa-477-37;AAC-Zinnia-500-19;AAC-Hyacinth-500-37;AAC-Dahlia-556.5-19;AAC-Mistletoe-556.5-37;AAC-Meadowsweet-600-37
Conductor Diameter - Maximum	0.893 in
Conductor Diameter - Minimum	0.522 in
Conductor Diameter Range	0.522 - 0.893
Conductor Type	<ul style="list-style-type: none"> • AAC • ACSR

Logistics

Pallet Quantity	324
-----------------	-----

Product Assets

[Catalogs - Substation Connectors \(SA\)](#)

[Video - Hubbell Power Systems 3D Portal to help with developing 3D models of substation connector products \(VI05050E0619\)](#)

[Video - Hubbell Power Systems Quick Ship \(VI05124E1018\)](#)



A proud member of the Hubbell Family.