


HUBBELL

Power Systems

Deadend, Straight line, Spring Loaded, Side Opening, 3/0 (7 STR) - 556 (37 STR) AL, 2/0 (6/1) - 556 (18/1) ACSR

By ANDERSON
Catalog # [ADEZ88N](#)



*Representative Image

Deadend, Straight line, Spring Loaded, Side Opening, 3/0 (7 STR) - 556 (37 STR) AL, 2/0 (6/1) - 556 (18/1) ACSR, Conductor Range 0.44 - 0.88 in, Fitting: None.

Features

- Captive hardware to prevent disassembly
- pivoting spring loaded keeper for easy conductor insertion
- Add "S" for Socket or "C" for Clevis Fitting Options

General

Fitting Type	None
Material	Aluminum
Material - Body	356 T6 Aluminum Alloy
Material - Hardware	Galvanized Steel
Material - Keeper	356 T6 Aluminum Alloy
Material - Pin (Cotter)	Stainless Steel
Material - Socket and Clevis	Ductile Iron, Galvanized
Material - Spring (on Eystem)	Stainless Steel
Product Category	Straight Line
Strength Rating - Ultimate	10000 lb
Body	
Style	ADEZ
Type	Bolted
U-Bolts	2 in
UPC	096359281191

Dimensions

Diameter - Bolt	0.5 in
Diameter - Pin	0.625 in
Length	10.81 in
Weight	3 lb
Width	1 in

Conductor Related

Conductor Compatibility

ACSR-Turkey-6-6/1;ACSR-Quail-2/0-6/1;ACSR-Pigeon-3/0-6/1;ACSR-Waxwing-266.8-18/1;ACSR-Partridge-266.8-26/7;ACSR-Ostrich-300-26/7;ACSR-Merlin-336.4-18/1;ACSR-Linnet-336.4-26/7;ACSR-Oriole-336.4-30/7;ACSR-Chickadee-397.5-18/1;ACSR-Brant-397.5-24/7;ACSR-Ibis-397.5-26/7;ACSR-Lark-397.5-30/7;ACSR-Pelican-477-18/1;ACSR-Flicker-477-24/7;ACSR-Hawk-477-26/7;ACSR-Osprey-556.5-18/1;ACSR-Brahma-203.2-16/19;AAC-Phlox-3/0-7;AAC-Oxlip-4/0-7;AAC-Valerian-250-19;AAC-Laurel-266.8-19;AAC-Daffodil-350-19;AAC-Canna-397.5-19;AAC-Cosmos-477-19;AAC-Syringa-477-37;AAC-Zinnia-500-19;AAC-Hyacinth-500-37;AAC-Dahlia-556.5-19;AAC-Mistletoe-556.5-37;AAAC 6201 Alloy-Anaheim-155.4-6/18;AAAC 6201 Alloy-Amherst-195.7-6/18;AAAC 6201 Alloy-Alliance-246.9-6/18

Conductor Diameter - Maximum	0.88
Conductor Diameter - Minimum	0.44
Conductor Diameter Range	0.44 - 0.88

Logistics

Pallet Quantity	300
-----------------	-----

Product Assets

[Catalogs - Distribution Connectors](#)

[Installation Manuals - ADEZ Series Aluminum Deadend](#)

[Recommended Installation Instructions](#)

[Literature - Ropes Course Industry Letter \(April 2021\)](#)

[Literature - Deadends For Overhead Connections](#)

[Sales Drawings - AL, DE Easy On Clamp FF # Adez-See Table](#)



A Hubbell brand

©2024 Hubbell Incorporated. All rights reserved
AN-ADEZ88N-SPEC-EN | REV 6/2024