

HUBBELL

Power Systems

Stud Connector, Bolted Aluminum, Stud to Tube

By ANDERSON
Catalog # [ADST120612](#)

Aluminum alloy stud connector is used to connect aluminum tubing to aluminum or copper equipment stud.



*Representative Image

Features

- Bolted Aluminum Stud to Tube
- Stud Diameter/Thread: 1-1/4"-12 to 3/4" IPS/EHIP Tube
- Clamping bolts have hex-stops for one-wrench installation.
- Material: Casting - 356-T6 aluminum alloy, Hardware - aluminum alloy, Contact sealant is factory installed in connector stud threads and is recommended for conductor installation.
- To specify 90 degree connector, add "90" to catalog number. Example: ADST14209012

General

| | |
|------------------------------|----------------|
| EU RoHS Indicator | No |
| Material | Aluminum |
| Material - Clamping Hardware | Aluminum Alloy |
| Number of Ground Braid Lug | 0 |
| Holes | |
| Number of Stud Threads | 12 |
| Type | Stud to Tube |
| UPC | 096359282129 |

Dimensions

| | |
|---------------------------|---------|
| Angle - Stud to Conductor | 180 ° |
| Base Hole Spacing | 0 in |
| Diameter - Base Holes | 0 in |
| Diameter - Bolt | 0 in |
| Diameter - Inside | 0 in |
| Diameter - Stud | 1.25 in |
| Length - Coupling | 0 in |
| Length Before Compression | 0 in |
| Weight | 1.47 lb |

Electrical Ratings

Maximum Current Rating Amps 0
Continuous

Conductor Related

Conductor Type Aluminum Bus

Product Assets

[Catalogs - Substation Connectors \(SA\)](#)
[Sales Drawings - C-1336 \(ADST Product Family\)](#)
[Video - Hubbell Power Systems 3D Portal to help with developing 3D models of substation connector products](#)
[Video - Hubbell Power Systems Quick Ship](#)



A Hubbell brand

©2024 Hubbell Incorporated. All rights reserved
AN-ADST120612-SPEC-EN | REV 6/2024