HUBBELL Power Systems

Coupler, Aluminum Bolted

By ANDERSON Catalog # AL456060

Aluminum alloy angle coupler for connecting aluminumaluminum or aluminum-copper tubing at 45 degrees.



*Representative Image

Features

- For 6" IPS/EHIPS Tubing Main to 6" IPS/EHIPS Tubing Tap
- 45 degree angle
- Material: Castings 356-T6 aluminum alloy, Hardware aluminum alloy
- Clamping bolts have hex stops for one-wrench installation.
- Contact sealant is recommended.

General

| Bolt Installation Torque | 480 in-Ibs |
|------------------------------|-----------------------|
| (Recommended) | |
| EU RoHS Indicator | No |
| Material | Aluminum |
| Material - Clamping Hardware | Aluminum Alloy |
| Туре | Tube to Tube Couplers |
| UPC | 096359347736 |
| | |

Dimensions

| Diameter - Clamping Hardware | 0.625 in |
|------------------------------|----------|
| Diameter - Rod / Tube | 6 in |
| Weight | 19.6 lb |

Electrical Ratings

Maximum Current Rating Amps See Technical Advisor Continuous

Conductor Related

Conductor Type Aluminum Bus

Product Assets

Catalogs - Substation Connectors (SA) Sales Drawings - C-2527 (AL45 Product Family) Video - Hubbell Power Systems 3D Portal to help with developing 3D models of substation connector products Video - Hubbell Power Systems Quick Ship



HUBBELL A Hubbell brand