HUBBELL
Power Systems

Cable Spacer, Aluminum

By ANDERSON
Catalog # APCS158

Aluminum Alloy, parallel cable spacer for maintaining aluminum cable clearance and preventing loose cable damage.

*Representative Image

Features

- 8 in Spacing
- Conductor Diameter Ranges: 1.289 - 1.459 inches
- Conductor Ranges: 1250 - 1600 MCM AAC and 1113-1272 MCM ACSR
- Material: Casting - 356-T6 aluminum alloy, Hardware - aluminum alloy
- Contact sealant is recommended.
- Recommended for slack spans only.
- For substation use only. Do not use for overhead transmission lines.

General

Catalog Number	APCS158
Material	Aluminum
Material - Clamping Hardware	Aluminum Alloy
Number of Ground Braid Lug Holes	0
Type	Cable Spacer
UPC	096359283775

Dimensions

Base Hole Spacing	0 in
Diameter - Base Holes	0 in
Diameter - Bolt	0 in
Diameter - Inside	0 in
Dimensions	2.12 in x 9.887 in x 1.133 in
Height	1.133 in
Length	2.12 in
Length - Coupling	0 in
Length Before Compression	0 in
Weight	2.28 lb
Width	9.887 in

Electrical Ratings

Maximum Current Rating Amps Continuous	0

Conductor Related

Conductor Compatibility	ACSR-Finch-1113-54/19;ACSR-Bunting-1192.5-45/7;ACSR-Grackle-1192.5-54/19;ACSR-Bittern-1272-45/7;ACSR-Pheasant-1272-54/19;ACSR-Dipper-1351.5-45/7;ACSR-Martin-1351.5-54/19;ACSR-Bobolink-1431-45/7;AAC-Narcissus-1272-61;AAC-Columbine-1351.5-61;AAC-Carnation-1431-61;AAC-Gladiolus-1510.5-61;AAC-Coreopsis-1590-61
Conductor Diameter - Maximum	1.459 in
Conductor Diameter - Minimum	1.289 in
Conductor Diameter Range	1.289 - 1.459
Conductor Spacing	8 in
Conductor Type	• AAC • ACSR

Logistics

Pallet Quantity	432

Product Assets

Catalogs - Substation Connectors (SA)
Sales Drawings - C-4936
Specifications - APCS158
Video - Hubbell Power Systems 3D Portal to help with developing 3D models of substation connector products
Video - Hubbell Power Systems Quick Ship

©2024 Hubbell Incorporated. All rights reserved