HUBBELL Power Systems

Terminal, Aluminum Bolted

By ANDERSON
Catalog # ASTF40D

Aluminum alloy terminal for connecting aluminum tubing to aluminum or copper flat pad combinations. Side formed tongues are standard to allow clearance for flush mounting. Clamping bolts will have hex stops for one wrench installation. Tongue holes have NEMA spacing. Contact sealant is recommended.

Features

- · Bolted tube to flat
- Tube size 4" IPS pad: 4 hole, 4 in
- Material: Castings-Aluminum alloy, Factory formed laminated shunts-Aluminum, Clamping hardware-Aluminum alloy

General

Catalog Number	ASTF40D
EU RoHS Indicator	No
Material	Aluminum
Material - Clamping Hardware	Aluminum Alloy
Number of Bolt Holes	4
Number of Pad Holes	4

Type Bolted Lugs & Terminals UPC 096359286363

Dimensions



*Representative Image

Angle - Pad 180 °
Diameter - Rod / Tube 4 in
Weight 5.488 lb
Width - Pad 4 in

Conductor Related

Conductor Type Aluminum Bus

Certifications And Compliance

Buy America(n) Qualified Contact Manufacturer

Product Assets

Catalogs - Substation Connectors (SA)
Sales Drawings - C-1660 (ASTF Product Family)
Specifications - ASTF40D
Video - Hubbell Power Systems 3D Portal to help with developing 3D models of substation connector products
Video - Hubbell Power Systems Quick Ship