

Coupler, Aluminum Bolted

By ANDERSON
Catalog # [ASTT2424](#)

Aluminum alloy, tubing to tubing, straight coupler for connecting aluminum-aluminum or aluminum-copper conductor combinations. Clamping bolts have hex stops for one wrench installation. Contact sealant is recommended.



*Representative Image

Features

- Coupler, Straight, Tube to Tube
- Material: Castings - aluminum alloy, Hardware - aluminum alloy
- 2-1/2" to 2-1/2" IPS/EHIPS tubes.

General

Bolt Installation Torque (Recommended)	300 in-lbs
Catalog Number	ASTT2424
EU RoHS Indicator	No
Material	Aluminum
Material - Clamping Hardware	Aluminum Alloy
Type	Tube to Tube Couplers
UPC	096359286578

Dimensions

Base Hole Spacing	0 in
Diameter - Clamping Hardware	0.5 in
Diameter - Rod / Tube	2-1/2 in
Weight	3.626 lb

Electrical Ratings

Maximum Current Rating Amps See Technical Advisor
Continuous

Conductor Related

Conductor Type	Aluminum Bus
----------------	--------------

Certifications And Compliance

Buy America(n) Qualified	BABA Compliant (All status valid till December 2024)
--------------------------	--

Logistics

Pallet Quantity 162

Product Assets

- Catalogs - Substation Connectors (SA)
- Sales Drawings - C-1338 (ASTT Product Family)
- Specifications - ASTT2424
- Video - Hubbell Power Systems 3D Portal to help with developing 3D models of substation connector products
- Video - Hubbell Power Systems Quick Ship