

Tee, Aluminum Bolted

By ANDERSON
Catalog # [ATCC1313](#)

Tee, Aluminum Bolted, Cable to Cable, MAIN: 715.5-1113 MCM ACSR (1.081-1.293 in. dia.), TAP: 715.5-1113 MCM ACSR (1.081-1.293 in. dia.)



*Representative Image

Features

- Castings are 356-T6 Aluminum Alloy
- Clamping Hardware is Aluminum Alloy
- Clamping bolts have hex-stops for one-wrench installation
- Cable contact inhibitor is recommended

General

EU RoHS Indicator	No
Material	Aluminum
Material - Clamping Hardware	Aluminum Alloy
Type	Bolted Tees
UPC	096359286752

Dimensions

Weight	2.058 lb
--------	----------

Conductor Related

Conductor Compatibility	ACSR-Redwing-715.5-30/19;ACSR-Cuckoo-795-24/7;ACSR-Drake-795-26/7;ACSR-Condor-795-54/7;ACSR-Mallard-795-30/19;ACSR-Ruddy-900-45/7;ACSR-Canary-900-54/7;ACSR-Rail-954-45/7;ACSR-Cardinal-954-54/7;ACSR-Ortolan-1033.5-45/7;ACSR-Curlew-1033.5-54/7;ACSR-Bluejay-1113-45/7;ACSR-Finch-1113-54/19;AAC-Cockscomb-900-37;AAC-Snapdragon-900-61;AAC-Magnolia-954-37;AAC-Goldenrod-954-61;AAC-Camellia-1000-61;AAC-Bluebell-1033.5-37;AAC-Larkspur-1033.5-61;AAC-Marigold-1113-61;AAC-Hawthorn-1192.5-61
Conductor Diameter (Main) - Maximum	1.293 in
Conductor Diameter (Main) - Minimum	1.081 in
Conductor Diameter (Main) Range	1.081 - 1.293
Conductor Diameter (Tap) - Maximum	1.108 in
Conductor Diameter (Tap) - Minimum	0.87 in
Conductor Type	<ul style="list-style-type: none"> • AAC • ACSR

Logistics

Pallet Quantity	432
-----------------	-----

Product Assets

[Catalogs - Substation Connectors \(SA\)](#)

[Sales Drawings - C-1279 \(ATCC Product Family\)](#)

[Video - Hubbell Power Systems 3D Portal to help with developing 3D models of substation connector products \(VI05050E0619\)](#)

[Video - Hubbell Power Systems Quick Ship \(VI05124E1018\)](#)



A proud member of the Hubbell Family.

©2024 Hubbell Incorporated. All rights reserved.
AN-ATCC1313-SPEC-EN | REV 1/2024