

Tee, Aluminum Bolted

By ANDERSON
Catalog # [ATCC66](#)

Tee, Aluminum Bolted, Cable to Cable, MAIN: #4-4/0 Str. ACSR (0.232-0.575 inch dia.), TAP: #4-4/0 Str. ACSR (0.232-0.575 inch dia.)



*Representative Image

Features

- Castings are 356-T6 Aluminum Alloy
- Clamping Hardware is Aluminum Alloy
- Clamping bolts have hex-stops for one-wrench installation
- Cable contact inhibitor is recommended

General

Material	Aluminum
Material - Clamping Hardware	Aluminum Alloy
Type	Bolted Tees
UPC	096359286967

Dimensions

Weight	0.882 lb
--------	----------

Conductor Related

Conductor Compatibility	ACSR-Swan-4-6/1;ACSR-Swanate-4-7/1;ACSR-Sparrow-2-6/1;ACSR-Sparate-2-7/1;ACSR-Robin-1-6/1;ACSR-Raven-1/0-6/1;ACSR-Quail-2/0-6/1;ACSR-Pigeon-3/0-6/1;ACSR-Penguin-4/0-6/1;AAC-Rose-4-7;AAC-Iris-2-7;AAC-Pansy-1-7;AAC-Poppy-1/0-7;AAC-Aster-2/0-7;AAC-Phlox-3/0-7;AAC-Oxlip-4/0-7;AAC-Valerian-250-19
Conductor Diameter (Main) - Maximum	0.575 in
Conductor Diameter (Main) - Minimum	0.232 in
Conductor Diameter (Main) Range	0.232 - 0.575
Conductor Diameter (Tap) - Maximum	0.575 in
Conductor Diameter (Tap) - Minimum	0.232 in
Conductor Type	<ul style="list-style-type: none"> • AAC • ACSR

Logistics

Pallet Quantity	840
-----------------	-----

Product Assets

[Catalogs - Substation Connectors \(SA\)](#)

[Video - Hubbell Power Systems 3D Portal to help with developing 3D models of substation connector products \(VI05050E0619\)](#)

[Video - Hubbell Power Systems Quick Ship \(VI05124E1018\)](#)