

HUBBELL

Power Systems

Tee, Aluminum Bolted

By ANDERSON

Catalog # [ATCF21301](#)

Aluminum alloy, cable to flat bar, tee for connecting aluminum-cable to aluminum or copper flat pad combinations. Flat pads are 3/8" thick with contact surface on one side. NEMA hole spacing is standard. Contact sealant is recommended.



*Representative Image

Features

- Tee, Aluminum Bolted, Cable to Flat, MAIN: 2500-3000 MCM AAC (1.824-2.00 in. dia.), TAP: 3x3 in. w/ 4 hole (NEMA C size pad)
- Castings are 356-T6 Aluminum Alloy
- Clamping Hardware is Aluminum Alloy
- Pads are 3/8" thick
- Contact inhibitor is recommended

General

EU RoHS Indicator	No
Material	Aluminum
Material - Clamping Hardware	Aluminum Alloy
Number of Ground Braid Lug Holes	0
Number of Pad Holes	4
Type	Tee, Bolted
UPC	096359287155

Dimensions

Base Hole Spacing	0 in
Diameter - Base Holes	0 in
Diameter - Bolt	0 in
Diameter - Inside	0 in
Length - Coupling	0 in
Length Before Compression	0 in
Weight	4.41 lb
Width - Flat Bar Tap	3 in

Electrical Ratings

Maximum Current Rating Amps 0
Continuous

Conductor Related

Conductor Compatibility	ACSR-Joree-2515-76/19
Conductor Diameter (Main) - Maximum	2 in
Conductor Diameter (Main) - Minimum	1.824 in
Conductor Diameter (Main) Range	1.824 - 2
Conductor Type	AAC ACSR

Product Assets

- [Catalogs - Substation Connectors \(SA\)](#)
- [Sales Drawings - C-7148 \(ATCF Product Family\)](#)
- [Video - Hubbell Power Systems 3D Portal to help with developing 3D models of substation connector products](#)
- [Video - Hubbell Power Systems Quick Ship](#)



A Hubbell brand

©2024 Hubbell Incorporated. All rights reserved
AN-ATCF21301-SPEC-EN | REV 6/2024