HUBBELL Power Systems

Tee, Aluminum Bolted

By ANDERSON Catalog # ATT151410

Aluminum alloy, angle tee for connecting aluminum-aluminum or aluminum-copper tubing combinations at 15 degrees. Clamping bolts have hex-stops for one wrench installation. Contact sealant is recommended.



Features

- Bolted Tee
- 15 degree angle
- Tube to tube
- 1-1/2 to 1 IPS/EHIPS tubes
- Material: Castings- Aluminum Alloy, Hardware- Aluminum Alloy

General

EU RoHS Indicator No
Material Aluminum
Material - Clamping Hardware Aluminum Alloy

Number of Ground Braid Lug

Holes

Type Tee, Bolted UPC 096359287650

Dimensions

Base Hole Spacing 0 in
Diameter - Base Holes 0 in
Diameter - Bolt 0 in
Diameter - Inside 0 in
Length - Coupling 0 in
Length Before Compression 0 in
Weight 2.352 lb

Electrical Ratings

Maximum Current Rating Amps 0 Continuous

Conductor Related

Conductor Type Aluminum Bus

Product Assets

Catalogs - Substation Connectors (SA)
Sales Drawings - C-4862 (ATT15 Product Family)
Video - Hubbell Power Systems 3D Portal to help with
developing 3D models of substation connector products
Video - Hubbell Power Systems Quick Ship

