HUBBELL Power Systems

Tee, Aluminum Bolted

By ANDERSON Catalog # ATTC106

Aluminum alloy, tubing to cable, tee for connecting aluminumaluminum or aluminum-copper conductor combinations. Clamping bolts have hex stops for one wrench installation. Contact sealant is recommended.



Features

- Tube to Cable, 1 IPS/EHIPS to 0.232-0.575 cable
- Material: Castings 356-T6 aluminum alloy, Hardware aluminum alloy.

General

EU RoHS Indicator No
Material Aluminum
Material - Clamping Hardware Aluminum Alloy
Number of Ground Braid Lug 0

Holes

Type Tee, Bolted UPC 096359288183

Dimensions

Base Hole Spacing 0 in
Diameter - Base Holes 0 in
Diameter - Bolt 0 in
Diameter - Inside 0 in
Length - Coupling 0 in
Length Before Compression 0 in
Weight 1.274 lb

Electrical Ratings

Maximum Current Rating Amps 0 Continuous

Conductor Related

Conductor Compatibility ACSR-Swan-4-6/1;ACSR-

Swanate-4-7/1;ACSR-Sparrow-2-6/1;ACSR-Sparate-2-7/1;ACSR-Robin-1-6/1;ACSR-Raven-1/0-6/1;ACSR-Quail-2/0-

6/1;ACSR-Pigeon-3/0-6/1;ACSR-Penguin-4/0-6/1;AAC-Rose-4-7;AAC-Iris-2-7;AAC-Pansy-1-7;AAC-Poppy-1/0-7;AAC-Aster-2/0-7;AAC-

Phlox-3/0-7;AAC-Oxlip-4/0-7;AAC-Valerian-250-19

0.232 in

Conductor Diameter (Tap) - 0.575 in

Maximum

Conductor Diameter (Tap) -

Minimum

Conductor Type Aluminum Bus

Product Assets

Catalogs - Substation Connectors (SA)
Sales Drawings - C-1587 (ATTC Product Family)
Video - Hubbell Power Systems 3D Portal to help with
developing 3D models of substation connector products
Video - Hubbell Power Systems Quick Ship

