HUBBELL
Power Systems

Tee, Aluminum Bolted

By ANDERSON
Catalog # ATTH2410

Aluminum alloy, tubing to tubing, tee for connecting aluminum-aluminum or aluminum-copper conductor combinations. Clamping bolts have hex stops for one wrench installation. Contact sealant is recommended.



*Representative Image

Features

- Tubing Main to Tubing Tap, Tubing Main-IPS/EHIPS-4", Tubing Tap-IPS/EHIPS -4
- Material: Castings- Aluminum Alloy, Clamping Hardware- Aluminum Alloy"

General

Catalog Number	ATTH2410
EU RoHS Indicator	No
Material	Aluminum
Material - Clamping Hardware	Aluminum Alloy
Number of Ground Braid Lug Holes	0
Type	Tee, Bolted
UPC	096359289050

Dimensions

Base Hole Spacing	0 in
Diameter - Base Holes	0 in
Diameter - Bolt	0 in
Diameter - Inside	0 in
Length - Coupling	0 in
Length Before Compression	0 in
Weight	2.352 lb

Electrical Ratings

Maximum Current Rating Amps Continuous	0

Conductor Related

Conductor Type	Aluminum Bus

Certifications And Compliance

Buy American Compliant	Contact Manufacturer

Product Assets

Catalogs - Substation Connectors (SA)
Sales Drawings - C-1589 (ATTH Product Family)
Specifications - ATTH2410
Video - Hubbell Power Systems 3D Portal to help with developing 3D models of substation connector products
Video - Hubbell Power Systems Quick Ship

©2024 Hubbell Incorporated. All rights reserved