

Bus Support, Aluminum Bolted

By ANDERSON Catalog # AUR245

Bus Support, Aluminum Bolted, Slip-Fit or Rigid, 2-1/2 IPS/EHIPS Tube to Insulator, 5 in BC.



*Representative Image

Aluminum Bus

Dimensions

Diameter - Bolt Circle 5 in Weight 5.488 lb

Conductor Related

Conductor Type

Product Assets

Catalogs - Substation Connectors (SA) Sales Drawings - C-4244 (AUR Product Family) Video - Hubbell Power Systems 3D Portal to help with developing 3D models of substation connector products (VI05050E0619)

Video - Hubbell Power Systems Quick Ship (VI05124E1018)

Features

- Caps may be rotated to provide slip-free or rigid clamping
- Stainless steel static eliminator springs are standard
- Clamping bolts have hex-stops for one-wrench installation
- Four Galv-Steel HH Bolts, lock washers and flat washers provided to mount to insulator cap.

General

| EU RoHS Indicator | No |
|------------------------------|--------|
| Material | Alumi |
| Material - Clamping Hardware | Alumi |
| Material - Mounting Hardware | Galva |
| Туре | Tube t |
| UPC | 09635 |

inum inum Alloy nized Steel to Insulator 59289739



©2024 Hubbell Incorporated. All rights reserved. AN-AUR245-SPEC-EN | REV 1/2024