

## Tee Copper Compression

By ANDERSON  
Catalog # [BCTCF025C](#)

"Terminal, Bolted Lug, Two Cables to Flat, 4-hole Pad, Straight, Used for AAC ACSR conductor, Conductor Range: 0.232"-0.575", Material: Castings-Aluminum alloy, Clamping Hardware-Aluminum alloy"



\*Representative Image

### Features

- "Tee for Connecting a continuous Copper Cable to Flat Pad"

### General

EU RoHS Indicator	No
Material	Copper
Number of Bolt Holes	4
Number of Pad Holes	4
Type	Tee, Copper Compression
UPC	096359291541

### Dimensions

Weight	4.508 lb
Width - Flat Bar Tap	3 in

### Conductor Related

Conductor Diameter (Main) - Maximum	0.575 in
Conductor Diameter (Main) - Minimum	0.575 in
Conductor Diameter (Main) Range	0.575 - 0.575
Conductor Type	Copper

### Product Assets

[Catalogs - Substation Connectors \(SA\)](#)

[Sales Drawings - C-5603 \(BCTCF Product Family\)](#)

[Video - Hubbell Power Systems 3D Portal to help with developing 3D models of substation connector products \(VI05050E0619\)](#)

[Video - Hubbell Power Systems Quick Ship \(VI05124E1018\)](#)